

198

Dependent Resurvey, Portion of South Boundary, T. 22 S., R. 63 E.

| Chains | |
|--|--|
| 60.60 | Point for reference monument bears N. 45° E., 45.4 lks.(30 ft.) dist. Set a 1 in. T-iron stake, 24 ins. long, 14 ins. in the ground, with a cadmium plated cap mkd. U. S. Bureau of Land Management Survey Corner RM 30 ft. 1957, and an arrow pointing toe the cor. |
| 66.90 | Wash, 1 ch. wide, 2 ft. deep, drains N. |
| 70.022 | Low flat spur, slopes NE. Point for the West-West 1/64 sec. cor. of secs. 4 and 33, at proportionate dist. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. |
| 70.90 | W W 1/64 <u>S33</u> S 4 1957 |
| 74.40 | Deposit broken glass 12 ins. below the surface of the ground and raise a collar of stone around the iron post. |
| 80.024 | Wash, 20 lks. wide, 2 ft. deep, drains N. |
| | Small gravelly spur, slopes NE. |
| | The cor. of secs. 4, 5, 32 and 33, which is mkd. by an iron post. 2 ins. diam. firmly set in the ground, mkd. and witnessed as defined in the 1931 resurvey record. |
| | Rebuild mound of stone, 3 ft. base, 2 ft. high, W. of cor. from which |
| | Point for reference monument bears N. 45° E., 45.4 lks.(30 ft.) dist. Set a 1 in. T-iron stake, 24 ins. long, 14 ins. in the ground, with a cadmium plated cap mkd. U. S. Bureau of Land Management Survey Corner RM 30 ft. 1957, and an arrow pointing to the cor. |
| | Point for reference monument bears N. 45° W., 45.4 lks.(30 ft.) dist. Set a 1 in. T-iron stake, 24 ins. long, 14 ins. in the ground, with a cadmium plated cap mkd. U. S. Bureau of Land Management Survey Corner RM 30 ft. 1957, and an arrow pointing to the cor. |
| | Land, slightly rolling. Soil, sandy clay loam. Timber, none. Undergrowth, creosote bush and sagebrush. |
| Dependent Resurvey, Portion of Subdivision, T. 22 S., R. 63 E. | |
| Resurvey of surveys executed by C. A. Magee in 1883 and independently resurveyed by Swanholm and Yundt in 1931, with the reestablishment of the resurvey made by Swanholm and Yundt in 1931. | |
| From the cor. of secs. 4, 5, 32 and 33 on the S. bdy. of the township. | |
| N. 0° 08' E., bet. secs. 32 and 33. | |
| Over slightly rolling land; desc. 35 ft. over NNW. slope, through moderately heavy undergrowth. | |
| 4.00 | Wash, 15 lks. wide, 6 ins. deep, drains N. 80° E. |
| 9.995 | Point for the South-South 1/64 sec. cor. of secs. 32 and 33, at proportionate dist. |