

Subdivision of Section 9, T. 22 S., R. 63 E.

	Chains	From the $\frac{1}{4}$ sec. cor. of secs. 9 and 16. N. $0^{\circ} 05'$ E., on the N-S center line. Over flood plain, through medium heavy undergrowth.
1.30		Wash, 15 lks. wide, 1 ft. deep, drains NW.
10.004		Point for the Centersouth-South 1/64 sec. cor. at proportionate dist. Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd. GS-S 1/64 S 9 1957
		Deposit broken glass 12 ins. below the surface of the ground, and raise a collar of stone around the iron post.
20.008		Point for the Center-South 1/16 sec. cor., at proportionate dist. Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd. C-S 1/16 S 9 1957
		Deposit broken glass 12 ins. below the surface of the ground, and raise a collar of stone around the iron post.
	from which	Point for reference monument bears N. 45° E., 60.6 lks.(40 ft.) dist. Set a 1 in. T-iron stake, 24 ins. long, 14 ins. in the ground, with a cadmium plated cap mkd. U. S. Bureau of Land Management Survey Corner RM 40 ft. 1957, and an arrow pointing to the cor.
		Point for reference monument bears N. 45° W., 60.6 lks.(40 ft.) dist. Set a 1 in. T-iron stake, 24 ins. long, 14 ins. in the ground, with a cadmium plated cap mkd. U. S. Bureau of Land Management Survey Corner RM 40 ft. 1957, and an arrow pointing to the cor.
20.30		Telephone line, bears N. 56° W. and S. 56° E.
22.00		Road, bears N. 56° W. and S. 56° E.
30.012		Point for the Centernorth-South 1/64 sec. cor., at proportionate dist. Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd. CN-S 1/64 S 9 1957
		Deposit broken glass 12 ins. below the surface of the ground, and raise a collar of stone around the iron post.
40.016		Intersect E-W center line.
		Point for the Center $\frac{1}{4}$ sec. cor. at proportionate dist. Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.