1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	Dependent Resurvey, S. Bdy., T. 23 S., R. 62 E.
Chains	
	Land, mountainous desert. Soil, gravel and rocks. Timber, none.
	N. 89° 32' W., along the S. bdy. of sec. 31.
	Desc. 100 ft. along S. slope of low spur.
40.04	Point for the ½ sec. cor. of sec. 31, T. 23 S., R. 62 E. only, at proportionate dist.; there is no remaining evidence of original cor.
	Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground to bedrock and in a mound of stone, 4 ft. base, to top, with brass cap mkd.
en e	T23S-R62E <u>½ S31</u>
	1959
	Desc. 70 ft. along gentle S. slope of spur.
61.60	Wash, drains N. 80° W.; desc. 25 ft. over gentle NW. slope, covered with large boulders.
80.23	The cor. of Tps. 23 and 24 S., Rs. 61 and 62 E., mkd. by an iron post, 3 ins. diam., conforming to the records.
.5	Land, mountainous. Soil, gravel and rocks. Timber, none.
	Independent Resurvey of a Portion of the Subdivision, T. 24 S., R. 62 E.
Same e James	Beginning the independent resurvey of the subdivisional lines at the standard cor. of sec. 35 and 36 on the S. bdy. of the Tp., Sixth Standard Parallel South, which is monumented with an iron post, 2 ins. diam. firmly set in the ground, mkd. and witnessed as described in the official record.
men on See worker	N. 0° 01' W., bet. secs. 35 and 36.
	Over nearly level flat plain through heavy undergrowth.
	Asc. 31 ft. over gradual ENE. slope.
2.20	Wash, 20 lks. wide, 1 ft. deep, drains NE.
9.50	Wash, 20 lks. wide, 1 ft. deep, drains NE.
12:20	Wash, 10 1ks. wide, 1 ft. deep; drains NE.
27.67	Wash, 15 lks. wide, 1 ft. deep, drains NE.
40.00	Point for the ½ sec. cor. of secs. 35 and 36, set an ironpost 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
3 n	