

Independent Resurvey, Portion of Subdivision, T. 24 S., R. 62 E.

Chains	
	N. 0° 01' W., bet. secs. 2 and 3.
	Over mountainous desert land; desc. 200 ft. over ledgy NE. slope; by triangulation, topography estimated.
10.00	Draw, drains NE.; asc. 300 ft. over steep E. slope.
30.40	Spur, projects NE.; desc. 190 ft. over N. slope. End of triangulation.
40.00	Point for the $\frac{1}{2}$ sec. cor. of secs. 2 and 3.
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 8 ins. in the ground and in a mound of stone, $3\frac{1}{2}$ ft. base, to top of cap, with brass cap mkd.
	T24S R62E
	$\frac{1}{2}$
	S 3 S 2
	1959
	Desc. 620 ft. over ledgy NE. slope; by triangulation, topography estimated.
49.10	Draw, drains E.; asc. 485 ft. over irregular S. slope.
56.40	Spur, projects NE.; desc. 420 ft. over N. slope.
70.30	Draw, drains NE.; asc. 220 ft. over S. slope.
80.00	Point for the $\frac{1}{16}$ sec. cor. of secs. 2 and 3.
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., on solid stone and in a mound of stone, 4 ft. base, to top of cap, with brass cap mkd.
	T24S R62E
	$\frac{1}{16}$
	S 3 S 2
	80.00
	1959
	Asc. 10 ft. over S. slope.
80.30	Top of spur, slopes E.; desc. 100 ft. over N. slope; end of triangulation.
85.10	Intersect the S. bdy. of T. 23 S., R. 62 E.
	Point for the closing cor. of secs. 2 and 3.
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam. over a cross (X) cut in solid stone and in a mound of stone, 4 ft. base, to top of cap, with brass cap mkd.
	T23S R62E
	S35
	S 2 S 3
	C C
	T24S R62E
	1959
	From this cor. the cor. of secs. 34 and 35, T. 23 S., R. 62 E. bears N. 89° 32' W., 17.03 chs. dist., an iron post, $2\frac{1}{2}$ ins. diam., described in the field notes of the dependent resurvey of the S. bdy. of T. 23 S., R. 62 E.
	Land, broken, mountainous.
	Soil, gravel and rocks.
	Timber, none.