

Independent Resurvey, Portion of Subdivision, T. 24 S., R. 62 E.

Chains	Set an iron post, 30 ins. long, 2½ ins. diam. on solid rock, over a cross (X) and in a mound of stone, 4 ft. base, to top, with brass cap mkd. T24S R62E ½ S 4 S 3 1959 Asc. 175 ft. over SW. slope. 49.00 Top of ascent on main divide, bears NW. and SE.; desc. 200 ft. along broken and ledgy E. slope. 62.50 Crest of ledges, bears N. and S. irregularly; desc. 360 ft. along broken E. slope, by traverse. 80.00 Point for the 1/16 sec. cor. of secs. 3 and 4 falls on inaccessible ledges, facing NE., and cannot be monumented. 82.49 Point selected for the witness 1/16 cor. of secs. 3 and 4. Set an iron post, 30 ins. long, 2½ ins. diam. on solid stone, over a cross (X) and in a mound of stone, 4 ft. base to top, with brass cap mkd. T24S R62E 1/16 S 4 S 3 80 W-C 1959 Desc. 25 ft. along broken E. slope. 85.89 Intersect the S. bdy. of T. 23 S., R. 62 E. Point for the closing cor. of secs. 3 and 4. Set an iron post, 30 ins. long, 2½ ins. diam. on solid limestone, over a cross (X) and in a mound of stone, 4 ft. base, to top, with brass cap mkd. T23S R62E S 34 S 4 S 3 C C T24S R62E 1959 From this cor. the cor. of secs. 33 and 34, T. 23 S., R. 62 W. bears N. 89° 32' W., 17.19 chs., dist., mkd. by an iron post, 2½ ins. diam., described in the field notes of the dependent resurvey of the S. bdy. of T. 23 S., R. 62 E. Land, broken mountain. Soil, gravel and rocks. Timber, none. Point for the N. ¼ sec. cor. of sec. 3 is on the S. bdy. of T. 23 S., R. 62 E. and is midpoint bet. the closing cor. of secs. 2 and 3, and the closing cor. of secs. 3 and 4. Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.
--------	--