

Independent Resurvey of Subdivisional Lines, T. 25 S., R. 62 E.

Chains

Superseding the survey executed by T. A. Magee, Deputy Surveyor, in 1882, (No original corners were found in the resurvey of the subdivisional lines of this township.)

From the cor. of secs. 1, 2, 35 and 36, on the S. bdy. of the Tp. N. 0° 01' W., bet. secs. 35 and 36.

Over nearly level flood plain, through scattered undergrowth.

Desc. 70 ft. over gradual NNE. slope.

40.00

Point for the ¼ sec. cor. of secs. 35 and 36.

Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.

T25S R62E

¼

S35|S36

1958

Raise a mound of stone, 3½ ft. base, 2½ ft. high, W. of cor.

Cont. over nearly level flood plain; desc. 70 ft. over gradual NNE. slope.

80.00

Point for the cor. of secs. 25, 26, 35 and 36.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T25S R62E

S26|S25

S35|S36

1958

Raise a mound of stone, 3½ ft. base, 2½ ft. high, W. of cor.

Land, nearly level flood plain.

Soil, sandy and gravelly, stony.

Timber, none.

Undergrowth, cactus, yucca and creosote bush.

From the cor. of secs. 25, 30, 31 and 36, on the E. bdy. of the Tp., which is mkd. with an iron post, 2½ ins. diam., firmly set in the ground, mkd. and witnessed as described in the official record.

S. 89° 58' W., bet. secs. 25 and 36.

Over nearly level land, through scattered undergrowth.

22.40

Wash, 30 lks. wide, 1½ ft. deep, drains N.

40.00

Point for the ¼ sec. cor. of secs. 25 and 36.

Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T25S R62E

¼ S25

S36

1958

Raise a mound of stone, 4 ft. base, 2½ ft. high, N. of cor.