

Independent Resurvey of Subdivisional Lines, T. 25 S., R. 62 E.

	Chains	N. 0° 01' W., bet. secs. 1 and 2. Over nearly level flood plain, through scattered undergrowth. Desc., 35 ft. over gradual N. slope.
18.50		Wash, 40 lks. wide, 1 ft. deep, drains NE.
35.00		Wash, 50 lks. wide, 2 ft. deep, drains NE.
40.00		Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 2. Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.
		T25S R62E $\frac{1}{4}$ S2 S1 1958
		Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
41.50		Wash, 30 lks. wide, 1 ft. deep, drains NE.
48.00		Wash, 20 lks. wide, 1 ft. deep, drains NE.
50.60		Wash, 10 lks. wide, 2 ft. deep, drains NE.
51.50		City of Los Angeles power line, 5 cables on steel towers, bears S. 57° W. and N. 57° E.
54.00		Graded road, bears N. 57° E. and S. 57° W.
56.30		City of Los Angeles power line, 5 cables on steel towers, bears S. 57° W. and N. 57° E.
58.20		Graded road, bears N. 57° E. and S. 57° W.
61.10		City of Los Angeles power line, 5 cables on steel towers, bears N. 57° E. and S. 57° W.
83.20		Wash, 10 lks. wide, 6 ins. deep, drains NE.
83.45		Intersect the S. bdy. of sec. 36, T. 24 S., R. 62 E. (Sixth Standard Parallel South). Point for the closing cor. of secs. 1 and 2. Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
		T24S R62E 33S36 S2 S1 C C T25S R62E 1958
		Raise a mound of stone, 4 ft. base, $2\frac{1}{2}$ ft. high, S. of cor.
		From this cor. the standard cor. of secs. 35 and 36, T. 24 S., R. 62 E., which is mkd. with an iron post, 2 ins. diam., firmly set in the ground, mkd. and witness as described in the official record, bears W. 5.08 chs. dist.
		Land, nearly level flood plain. Soil, sandy and gravelly, stony. Timber, none. Undergrowth, cactus and creosote bush.