

## Independent Resurvey of Subdivisional Lines, T. 25 S., R. 62 E.

Chains	
30.00	Road, bears N. 19° 40' E. and S. 19° 40' W.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 2 and 3.
	Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T25S R62E $\frac{1}{4}$ S3 S2 1958
	Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
	Cont. over nearly level land; desc. 17 ft. over gradual NE. slope.
42.00	Wash, 15 lks. wide, 1 ft. deep, drains NE.
56.00	Wash, 15 lks. wide, 6 ins. deep, drains NE.
83.36	Intersect the S. bdy. of sec. 35, T. 24 S., R. 62 E. (Sixth Standard Parallel South). Point for the closing sec. cor. of secs. 2 and 3.
	Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T24S R62E S35 S3 S2 C C T25S R62E 1958
	Raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor.
	From this cor. the standard cor. of secs. 34 and 35, T. 24 S., R. 62 E., which is mkd. with an iron post, 2 ins. diam., firmly set in the ground, mkd. and witnessed as described in the official record, bears West 5.05 chs. dist.
	Land, nearly level. Soil, sandy and gravelly, stony. Timber, none. Undergrowth, cactus and creosote bush.
	The point for the $\frac{1}{4}$ sec. cor. of sec. 2 only, on the N. bdy. of the Tp. is at midpoint between the closing cor. of secs. 1 and 2 and the closing cor. of secs. 2 and 3.
	At the cor. point
	Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T24S R62E $\frac{1}{4}$ S2 T25S R62E 1958
	Raise a mound of stone, 3 ft. base, 2 $\frac{1}{2}$ ft. high, S. of cor.
	From this cor. the std. cor. of secs. 35, T. 24 S., R. 62 E. is mkd. with an iron post, 1 in. diam., firmly set in the ground, mkd. and witnessed as described in the official record, bears West 5.07 chs. dist.