

Independent Resurvey of Subdivisional Lines, T. 25 S., R. 62 E.

Chains	
32.60	Wash, 20 lks. wide, 1½ ft. deep, drains NE.
40.01	Point for the ¼ sec. cor. of secs. 3 and 10. Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd. T25S R62E S 3 ¼ S10 1958 Raise a mound of stone, 3½ ft. base, 2½ ft. high, N. of cor.
45.40	Wash, 50 lks. wide, 1½ ft. deep, drains NE.; cont. ascent; asc. 22 ft. over gradual NE. slope.
58.80	Wash, 25 lks. wide, 2 ft. deep, drains NE.
65.50	Wash, 20 lks. wide, 1 ft. deep, drains NE.
80.02	The cor. of secs. 3, 4, 9 and 10. Land, nearly level flood plain. Soil, sandy and gravelly, stony. Timber, none. Undergrowth, cactus and creosote bush.
	N. 0° 02' W., bet. secs. 3 and 4. Over nearly level flood plain, through scattered undergrowth. Desc. 18 ft. over gradual NE. slope.
.90	Wash, 10 lks. wide, 10 ins. deep, drains NE.
9.50	Wash, 15 lks. wide, 10 ins. deep, drains NE.
25.82	Telephone and Power line, 5 cables on steel towers, bears N. 50° 14' E. and S. 50° 14' W.
26.50	Road, improved, bears N. 50° 14' E. and S. 50° 14' W.
40.00	Point for the ¼ sec. cor. of secs. 3 and 4. Set an iron post, 30 ins. long, 2½ ins. diam., 8 ins. in the ground to solid rock, and in a mound of stone to top, with brass cap mkd. T25S R62E S 4 ¼ S3 1958 Raise a mound of stone, 3½ ft. base, 2½ ft. high, W. of cor. Cont. over nearly level land; asc. 46 ft. over gradual SE. slope.
83.41	Intersect the S. bdy. of sec. 34, T. 24 S., R. 62 E. (Sixth Standard Parallel South). Point for the closing cor. of secs. 3 and 4. Set an iron post, 30 ins. long, 2½ ins. diam., 12 ins. in the ground to solid rock, in a mound of stone to top, with brass cap mkd.