

397

Independent Resurvey of Subdivisional Lines, T. 25 S., R. 62 E.

Chains 71.94	Wash, 60 lks. wide, 5 ft. deep, drains SE.
80.00	Wash, 5 chs. wide, 3 ft. deep, drains SE.
83.46	Intersect S. bdy. of sec. 33, T. 24 S., R. 62 E. (Sixth Standard Parallel South), N. bdy. of T. 25 S., R. 62 E. Point for the closing cor. of secs. 4 and 5. Set an iron post, 30 ins. long, 2½ ins. diam., 8 ins. in the ground to solid rock, in a mound of stone to top, with brass cap mkd. T24S R62E S33 S5 S4 C C T25S R62E 1958 From this cor. the standard cor. of secs. 32 and 33, T. 24 S., R. 62 E., which is mkd. with an iron post, 2 ins. diam., firmly set in the ground, mkd. and witnessed as described in the official record, bears West, 5.11 chs. dist. Land, nearly level. Soil, sandy and gravelly, stony. Timber, none. Undergrowth, cactus, yucca and creosote bush.
	The point for the ¼ sec. cor. of sec. 4 only, on the N. bdy. of the Tp., is at midpoint bet. the closing cor. of secs. 3 and 4 and the closing cor. of secs. 4 and 5, T. 25 S., R. 62 E. At the cor. point Set an iron post, 30 ins. long, 2½ ins. diam., 8 ins. in the ground to solid rock, in a mound of stone to top, with brass cap mkd. T24S R62E ¼ S4 T25S R62E 1958 Raise a mound of stone, 4 ft. base, 2½ ft. high, W. of the cor. From this point the standard ¼ sec. cor. of sec. 33, T. 24 S., R. 62 E., monumented by an iron post, 1 in. diam., bears West 5.085 chs. dist.
	From the cor. of secs. 5, 6, 31 and 32, on the S. bdy. of the Tp. N. 0° 03' W., bet. secs. 31 and 32. Over nearly level flood plain, through scattered undergrowth; desc. 110 ft. over gradual NNE. slope.
24.50	Wash, 30 lks. wide, 2 ft. deep, drains NNE.
40.00	Point for the ¼ sec. cor. of secs. 31 and 32. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.