

Independent Resurvey of Subdivisional Lines, T. 25 S., R. 62 E.

Chains	West, bet. secs. 30 and 31. Over nearly level flood plain, through scattered undergrowth.
1.50	Wash, 35 lks. wide, 1 ft. deep, drains NNW.
9.00	Wash, 25 lks. wide, 1 ft. deep, drains N.
16.00	Wash, 30 lks. wide, 1 ft. deep, drains NNE.
29.00	Wash, 35 lks. wide, 1½ ft. deep, drains NNE.
34.00	Wash, 40 lks. wide, 2 ft. deep, drains NNE.
38.80	Wash, 35 lks. wide, 2 ft. deep, drains NNE.
40.00	Point for the ¼ sec. cor. of secs. 30 and 31. Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground to solid rock, in a collar of stone, with brass cap mkd. T25S R62E ¼ S30 S31 1958 Raise a mound of stone, 3½ ft. base, 2½ ft. high, N. of cor. Cont. over nearly level flood plain.
45.10	Wash, 30 lks. wide, 2 ft. deep, drains NNE.
57.00	Wash, 50 lks. wide, 3 ft. deep, drains NNE.
68.40	Wash, 35 lks. wide, 3 ft. deep, drains NNE.
79.95	Wash, 10 lks. wide, 3 ft. deep, drains NNE.
80.00	Point for the 1/16 sec. cor. of secs. 30 and 31. This point falls in a deep wash and is deemed unsafe for the cor. and is not monumented.
80.25	Point selected for the witness 1/16 sec. cor. of secs. 30 and 31. Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground to solid rock, in a collar of stone to top, with brass cap mkd. T25S R62E 1/16 S30 W 80.25 S31 C 1958 Raise a mound of stone, 3½ ft. base, 2 ft. high, W. of cor.
100.64	Intersect E. bdy. of sec. 25, T. 25 S., R. 61 E. and W. bdy. of T. 25 S., R. 62 E. Point for the closing cor. of secs. 30 and 31. Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground to solid rock, in a mound of stone to top, with brass cap mkd. T25S R61E R62E S25 S30 C S31 C 1958 From this cor. the original cor. of secs. 25, 30, 31 and 36, hereinbefore described, which now functions for the cor. of secs. 25 and 26 only, T. 25 S., R. 61 E., bears S. 0° 38' E., 3.75 chs. dist.