

Independent Resurvey of Subdivisional Lines, T. 25 S., R. 62 E.

Chains	
	Raise a mound of stone, 3½ ft. base, 2 ft. high, N. of cor. Cont. over nearly level land; asc. 65 ft. over gradual NE. slope.
80.00	Point for the 1/16 sec. cor. of secs. 19 and 30. Set an iron post, 30 ins. long, 2½ ins. diam., 8 ins. in the ground to solid rock, in a mound of stone to top, with brass cap mkd. <div>T25S R62E 1/16 S19 80.00 S30 1958</div>
89.00	Raise a mound of stone, 4 ft. base, 2½ ft. high, W. of cor. Wash, 50 lks. wide, 3 ft. deep, drains NE.
100.25	Intersect the E. bdy. of sec. 24, T. 25 S., R. 61 E. and point for the closing cor. of secs. 19 and 30, on the W. bdy. of the Tp. Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground to solid rock, in a mound of stone to top, with brass cap mkd. <div>T25S25S R62E R62E R61E S19 C S24 S30 C 1958</div> <p>From this cor. the cor. of secs. 24 and 25, T. 25 S., R. 61 E., hereinbefore described, bears S. 0° 35' W., 1.60 chs. dist.</p> <p>Land, nearly level. Soil, sandy and gravelly, stony. Timber, none. Undergrowth, cactus, yucca and creosote bush.</p>
	The point for the ¼ sec. cor. of sec. 30 is at midpoint bet. the closing cor. of secs. 30 and 31 and the closing cor. of secs. 19 and 30. At the cor. point Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground to solid rock, in a mound of stone to top, with brass cap mkd. <div>T25S R62E R61E ¼ S30 1958</div> <p>From this cor. the ¼ sec. cor. of sec. 25, T. 25 S., R. 61 E., hereinbefore described, bears S. 0° 53' W., 2.60 chs. dist.</p>
	From the cor. of secs. 19, 20, 29 and 30. N. 0° 03' W., bet. secs. 19 and 20. Over nearly level flood plain, through scattered undergrowth; desc. 68 ft. over gradual NNE.
10.10	Wash, 2 chs. wide, 2 ft. deep, drains NE.
27.00	Wash, 25 lks. wide, 4 ft. deep, drains NE.