

405

Independent Resurvey of Subdivisional Lines, T. 25 S., R. 62 E.

Chains	
79.00	Base of steep rocky slope, bears NNE. and SSW.; asc. 50 ft. over steep E. slope.
80.00	Point for the 1/16 sec. cor. of secs. 18 and 19. Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground to solid rock, and in a mound of stone to top, with brass cap mkd. <div>T25S R62E 1/16 S18 80.00 S19 1958</div> Cont. ascent; asc. 275 ft. over steep rocky E. slope.
87.00	Top of spur, slopes NNE.; desc. 34 ft. over NNW. slope.
100.00	Bottom of descent; begin ascent; asc. 43 ft. over ENE. slope.
101.42	Intersect the E. bdy. of sec. 13, T. 25 S., R. 61 E. and point for the closing cor. of secs. 18 and 19 on the W. bdy. of the Tp. At the cor. point Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground to solid rock, and in a mound of stone to top, with brass cap mkd. <div>T25S R62E R61E S18 C S13 S19 C 1958</div> From this cor. the cor. of secs. 13 and 24, T. 25 S., R. 61 E., herein- before described, bears S. 3° 57' W., 38.3 lks. dist. Land, nearly level flood plain. Soil, sand and gravelly, stony. Timber, none. Undergrowth, cactus, yucca and creosote bush.
	 The point for the ¼ sec. cor. of sec. 19 on the W. bdy. of the Tp. is at midpoint bet. the closing cor. of secs. 19 and 30, and the clos- ing cor. of secs. 18 and 19. At the cor. point Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground to solid rock, and in a mound of stone to top, with brass cap mkd. <div>T25S R62E R61E ¼ S19 1958</div> From this cor. the ¼ sec. cor. of sec. 24, T. 25 S., R. 61 E., herein- before described, bears S. 2° 25' E., 62.3 lks. dist.