

Dependent Resurvey, W. Bdy., T. 25 S., R. 65 E.

Chains

Dependent Resurvey of the West Boundary, T. 25 S., R. 65 E.

Reestablishment of the survey executed by T. A. Magee, Deputy Surveyor, in 1882.

The original corner for Tps. 25 and 26 S., Rs. 64 and 65 E., the original closing corner of T. 25 S., Rs. 64 and 65 E., on the S. bdy. of sec. 36, T. 24 S., R. 64 E. (Sixth Standard Parallel South), were recovered.

The retracement for the dependent resurvey of the W. bdy., T. 25 S., R. 65 E., shows the bdy. to be defective in alignment and measurement, thus requiring that the original closing corner of T. 25 S., Rs. 64 and 65 E., be reestablished to function as the northwest corner of T. 25 S., R. 65 E., only, and the reestablishment of corners, on the W. bdy. of T. 25 S., R. 65 E., only, at proportionate distance between the original corners.

The corner of secs. 25 and 36, on the E. bdy., T. 25 S., R. 64 E., is reestablished on the W. bdy. of T. 25 S., R. 65 E. at a point 80.00 chs. in northing from the established 1941 independent resurvey corner of Tps. 25 and 26 S., Rs. 63 and 64 E., which has been remarked to function for the corner of Tps. 25 and 26 S., R. 63 E., only. All other sec. and $\frac{1}{2}$ sec. cors. on the E. bdy. of T. 25 S., R. 64 E., will be established on the line at intervals of 40.00 chs. from the cor. of secs. 25 and 36, with fractional measurement in the south half of the E. bdy. of sec. 36, and the N. half of the E. bdy. of sec. 1.

The original cor. of Tps. 25 and 26 S., Rgs. 64 and 65 E., which is marked with a granite stone, 24 x 18 x 12 ins., firmly set in the ground, marked and witnessed as described in the 1882 survey record.

At the corner point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 10 ins. in the ground, to solid rock, and in a mound of stone to top, with brass cap mkd.

T25S
R64E R65E
S36 | S31
S 1 | S 6
T26S
1959

Reset the original corner stone alongside the iron post.

N. $1^{\circ} 12'$ E., on true line, along the W. bdy. of sec. 31.

Over heavily rolling mountainous land, through scattered undergrowth; asc. 233 ft. over steep, rocky, S. slope.

6.75 Top of spur, slopes ESE.; desc. 28 ft. over NE. slope.

8.82 Point for the $\frac{1}{16}$ sec. cor. of sec. 36, only, established at a point 80.00 chs. in southing from the cor. of secs. 25 and 36.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 4 ins. in the ground, to solid rock, and in a mound of stone to top, with brass cap mkd.

T26S
R64E
1/16 | R65E
S36 |
1959

Cont. descent; desc. 113 ft. over NE. slope.