

## Independent Resurvey, Subdivisional Lines, T. 25 S., R. 64 E.

Chains

82.00 Spur, sloping S.; desc. 60 ft. over E. slope.

84.80 Wash, near head, drains S.; asc. 60 ft. over W. slope.

88.00 End of triangulation on spur, sloping S.

88.64 The cor. of secs. 1 and 12 on the E. bdy.

Land, broken with series of spurs and washes.

Soil, boulder-strewn rocky silt.

Timber, none.

Undergrowth, creosote bush, catclaw acacia and several species of cacti, with the cholla family predominating.

From the cor. of secs. 1, 2, 11 and 12.

North, bet. secs. 1 and 2, on sectional guide meridian.

Over steep SW. slope.

By triangulation asc. 600 ft. over steep boulder-strewn SW. slope.

34.00 Broken spur, sloping SE. from high point to the NW.; thence along boulder-strewn NE. slope.

40.00 Point for the  $\frac{1}{2}$  sec. cor. of secs. 1 and 2.Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 6 ins. in the ground and in a mound of stone, 4 ft. base to brass cap mkd.

T25S R64E

 $\frac{1}{2}$ 

S 2 | S 1

1959

Cont. along boulder strewn E. slope.

44.20 End of triangulation on low spur sloping E.; desc. 620 ft. along boulder-strewn NE. slope.

84.37 Intersect the Sixth Standard Parallel South.

Point for the closing cor. of secs. 1 and 2.

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 6 ins. in the ground and in a mound of stone, 4 ft. base to brass cap mkd.

T24S R64E

S36

C | C

S 2 | S 1

T25S R64E

1959

From this cor. the standard cor. of secs. 35 and 36, mkd. by an iron post, 2 ins. diam., set, mkd. and witnessed as described in the official record, bears W. 0.66 chs. dist.

U.S.G.S triangulation "Peeper"; mkd. by a brass cap firmly set in cement, bears S.  $7^{\circ} 18' W.$ , 39.788 chs. dist.

Land, broken, ledgy slopes.

Soil, boulder-strewn rocky silt.

Timber, none.

Undergrowth, creosote bush, catclaw acacia and several species of cacti, with the cholla family predominating.