

Independent Resurvey, Subdivisional Lines, T. 25 S., R. 64 E.

Chains	<p>Asc. 50 ft. over NE. slope.</p>
5.00	Ridge, bears NW. and SE.; desc. 280 ft. over SW. slope.
25.50	Wash, 1.00 ch. wide, 1 ft. deep, drains N. 10° W.; asc. 170 ft. over E. slope.
37.00	Spur, sloping N. 10° W.; desc. 30 ft. over W. slope.
40.00	<p>Point for the ¼ sec. cor. of secs. 3 and 10.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 4 ins. in the ground and in a mound of stone, 4 ft. base to brass cap mkd.</p> <p style="text-align: center;">T25S R64E $\frac{1}{4}$ $\frac{S\ 3}{S10}$ 1959</p> <p>Cont. to desc. 80 ft. over steep W. slope.</p>
44.00	Wash, drains N. 5° W.
48.50	Wash, drains N. 10° E.
80.00	The cor. of secs. 3, 4, 9 and 10.
	<p>Land, broken to nearly level.</p> <p>Soil, rocky, sandy silt.</p> <p>Timber, none.</p> <p>Undergrowth, creosote bush and several species of cacti, with large tree-like yuccas predominating.</p>
	<p>From the cor. of secs. 3, 4, 9 and 10</p> <p>N. 0° 01' W., bet. secs. 3 and 4.</p> <p>Over alluvial fan, sloping N.</p> <p>Desc. 40 ft.</p>
9.00	Wash, drains N. 20° E.
40.00	<p>Point for the ¼ sec. cor. of secs. 3 and 4.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T25S R64E $\frac{1}{4}$ $\frac{S\ 4\ S\ 3}{1959}$</p> <p>Raise a mound of stone, 4 ft. base, 2 ft. high, W. of monument.</p> <p>Cont. to desc. 50 ft. over N. sloping alluvial fan.</p>
83.98	<p>Intersect the Sixth Standard Parallel South.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 26 ins. in the ground with brass cap mkd.</p> <p style="text-align: center;">T24S R64E $\frac{S34}{S\ 4\ S\ 3}$ C C T25S R64E 1959</p> <p>From this cor., the standard cor. of secs. 33 and 34, T. 24 S., R. 64 E., mkd. by an iron post, 2 ins. in diam., firmly set in the ground, with brass cap mkd. and witnessed as described in the official record, bears W. .73 chs. dist.</p>