

486

T. 26 S., R. 62 E.

## Chains

The original corner of Tps. 26 and 27 S., Rs. 62 and 63 E., which was marked with a basalt stone, 20x16x8 ins., firmly set in the ground, marked and witnessed as defined in the 1882 survey record, was found and destroyed, when the independent resurvey corner of Tps. 26 and 27 S., Rs. 62 and 63 E., was established in 1940-1941.

The position for the original corner of Tps. 26 and 27 S., Rs. 62 and 63 E., was recovered and remonumented.

At the cor. point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.

T26S	R62E
S 36	
S 1	
T27S	
R62E	
1959	

Bury the original cornerstone, alongside the iron post, and raise a mound of stone, 4 ft. base,  $2\frac{1}{2}$  ft. high, SW. of cor.

From this cor., the independent resurvey cor. of Tps. 26 and 27 S., Rs. 62 and 63 E., established in 1940-1941, which is marked with an iron post, 3 ins. diam., firmly set in the ground, marked and witnessed as defined in the 1940-1941 independent resurvey record, bears S.  $75^{\circ}55'$  E., 7.26 chs. dist.

The independent resurvey cor. of T. 26 and 27 S., Rs. 62 and 63 E., will now function for the cor. of T. 26 and 27 S., Rs. 63 E.

I delete all of the markings on the iron post monument, and remark the cor. to read

T 26 S	
R 63 E	
S 31	
S 6	
T 27 S	
R 63 E	
1959	

Rebuild the mound of stone, 4 ft. base,  $2\frac{1}{2}$  ft. high, E. of cor.

Retracement of a Portion of the West Boundary of T. 26 S., R. 63 E., Independently Resurveyed by Wilson McConkie and Alvyn C. Alberga in 1940

From the cor. which now functions for the cor. of T. 26 and 27 S., R. 63 E.

North, on the true line, on the west bdy. of sec. 31, T. 26 S., R. 63 E.

1.767

The true point for the establishment of the SE. cor. of T. 26 S., R. 62 E. This point is established E. of the original cor. of Tps. 26 and 27 S., Rs. 62 and 63 E., which has been remonumented and now functions as the NE. cor. of T. 27 S., R. 62 E. At the point of intersection with the W. bdy. of sec. 31, T. 26 S., R. 63 E.

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 10 ins. in the ground, to solid rock, and in a mound of stone to top, with brass cap mkd.

T 26 S	
R 62 E	T 26 S
S 36	
	R 63 E
	S 31
1959	