

494

Dependent Resurvey of the N. Bdy., T. 27 S., R. 62 E.

Chains

- 36.36 Improved road, oil surfaced, bears N. 10°49' E., and S. 10°49' W.
- 37.31 Southern California Edison Company, power line, 5 cables on steel towers, bears N. 10°49' E., and S. 10°49' W.
- 40.41 Southern California Edison Company, power line, 5 cables on steel towers, bears N. 10°49' E., and S. 10°49' W.
- 41.15 Point originally established for the cor. of secs. 5, 6, 31 and 32, at proportionate dist. There is no remaining evidence of the original cor. This cor. will now function for the cor. of secs. 5 and 6, only.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 26 S R 62 E
S 31

S 6 | S 5

T 27 S R 62 E

1959

Raise a mound of stone, 4 ft. base, 2½ ft. high, S. of cor.

Land, nearly level.

Soil, sandy and gravelly, stony.

Timber, none.

Undergrowth, cactus, yucca, and creosote bush.

S. 89°39' W., along the N. bdy. of sec. 6, (S. bdy. of sec. 31, T. 26 S., R. 62 E.).

Over gently rolling land, through medium heavy undergrowth.

- 1.73 Wash; 100 lks. wide, 2 ft. deep, drains NE., asc. 76 ft. over gradual NNE. slope.

- 22.30 Point for the ¼ sec. cor. of sec. 31, only.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 26 S R 62 E
¼ S 31

T 27 S R 62 E

1959

Raise a mound of stone, 4 ft. base, 2½ ft. high, N. of cor.

Continue over gently rolling land, asc. 83 ft. over NNE. slope.

- 41.00 Wash, 100 lks. wide, 3 ft. deep, drains NE.

- 41.15 Point originally established for the ¼ sec. cor. of secs. 6 and 31, at proportionate dist. There is no remaining evidence of the original cor. This cor. will now function for the ¼ sec. cor. of sec. 6, only.

Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground to solid rock, and in a mound of stone to top, with brass cap mkd.