

Dependent Resurvey of the E. Bdy., T. 26 S., R. 61 E.

Chains

Land, heavily rolling.
Soil, sandy and gravelly, stony.
Timber, none.
Undergrowth, cactus, yucca and creosote bush.

N. 0° 08' E., along the E. bdy. of sec. 1.

Over moderately heavily rolling land; through scattered undergrowth; asc. 121 ft. over a steep, rocky SE. slope.

5.62 Top of spur, slopes NE.; desc. 68 ft. over NW. slope.

16.48 Top of spur, slopes NE.; desc. 110 ft. over NE. slope.

28.70 Bottom of steep slope; cont. over nearly level land.

35.67 Wash, 80 lks. wide, 5 ft. deep, drains NE.; asc. 20 ft. over ESE. slope.

40.87 The original $\frac{1}{4}$ sec. cor. of secs. 1 and 6, which is marked with a basalt stone, 14x10x6 ins., firmly set in the ground, and in a mound of stone, marked and witnessed as defined in the 1882 survey record. This cor. will now function for the $\frac{1}{4}$ sec. cor. of sec. 1 only.

At the cor. point

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 6 ins. in the ground, to solid rock, and in a mound of stone to top, with brass cap mkd.

T 26 S
R 61 E
 $\frac{1}{4}$ R 62 E
S 1
1959

Reset the original cornerstone alongside the iron post and raise a mound of stone, 4 ft. base, 2 $\frac{1}{2}$ ft. high, W. of cor.

N. 1° 47' W., beginning new measurement.