

Independent Resurvey of the Subdivisional Lines, T. 26 S., R. 62 E.

Chains

T 26 S R 62 E
S 19
1/16 ————— 80.00
S 30
1959

Continue over gently rolling land; desc. 61 ft. over W. slope.

89.70 Wash, 30 lks. wide, 3 ft. deep, drains N., asc. 262 ft. over steep, rocky, E. slope.

98.77 Intersect E. bdy. of sec. 24, T. 26 S., R. 61 E.

Point for the closing cor. of secs. 19 and 30.

Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground, to solid rock, and in a mound of stone to top, with brass cap mkd.

T 26 S
R 62 E
R 61 E | S 19 C
S 24 | S 30 C
1959

From this cor., the cor. of secs. 24 and 25, T. 26 S., R. 61 E., which is marked with an iron post, 2½ ins. diam., hereinbefore described bears S. 0°01' W., 12.50 chs. dist.

Land, gently rolling.
Soil, sandy and gravelly, stony.
Timber, none.
Undergrowth, cactus, yucca, and creosote bush.

The point for the W¼ sec. cor. of sec. 30 is at midpoint and on the W. bdy. of the T.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 8 ins. in the ground, to solid rock, and in a mound of stone to top, with brass cap mkd.

T 26 S
R 62 E
R 61 E | ¼
S 30
1959

From this cor., the ¼ sec. cor. of sec. 25, T. 26 S., R. 61 E., which is marked with an iron post, 2½ ins. diam., hereinbefore described, bears S. 0°01' W., 13.16 chs. dist.

From the cor. of secs. 19, 20, 29, and 30.

N. 0°03' W., bet. secs. 19 and 20.

Over nearly level land, through medium heavy undergrowth; desc. 30 ft. over gradual NNE. slope.