

Independent Resurvey of the Subdivisional Lines, T. 26 S., R. 62 E.

Chains

80.00 Point for the 1/16 sec. cor. of secs. 18 and 19.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 6 ins. in the ground, to solid rock; and in a mound of stone to top, with brass cap mkd.

T 26 S R 62 E

S 18

1/16 ——— 80.00

S 19

1959

Continue ascent; asc. 27 ft. over NNE. slope.

98.70. Intersect E. bdy. of sec. 13, T. 26 S., R. 61 E.

Point for the closing cor. of secs. 18 and 19.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 8 ins. in the ground, to solid rock, and in a mound of stone to top, with brass cap mkd.

T 26 S

R 61 E | R 62 E

S 13 | S 18 C

S 19 C

1959

From this cor., the cor. of secs. 13 and 24, T. 26 S., R. 61 E., which is marked with an iron post, $2\frac{1}{2}$ ins. diam., hereinbefore described bears S. $0^{\circ}43'$ E., 11.21 chs. dist.

Land, nearly level.

Soil, sandy and gravelly, stony.

Timber, none.

Undergrowth, cactus, yucca, and creosote bush.

The point for the $\frac{1}{4}$ sec. cor. of sec. 19, is at midpoint and on the W. bdy. of the T.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 6 ins. in the ground, to solid rock, and in a mound of stone to top, with brass cap mkd.

T 26 S

R 61 E | R 62 E

 $\frac{1}{4}$

S 19

1959

From this cor., the $\frac{1}{4}$ sec. cor. of sec. 24, T. 26 S., R. 61 E., which is marked with an iron post, $2\frac{1}{2}$ ins. diam., hereinbefore described, bears S. $0^{\circ}01'$ W., 11.85 chs. dist.

From the cor. of secs. 17, 18, 19, and 20.

N. $0^{\circ}03'$ W., bet. secs. 17 and 18.