

Independent Resurvey of the Subdivisional Lines, T. 26 S., R. 62 E.

Chains	
56.00	Wash, 30 lks. wide, 9 ins. deep, drains N.
80.00	The cor. of secs. 5, 6, 7, and 8. Land, nearly level. Soil, sandy and gravelly, stony. Timber, none. Undergrowth, cactus, yucca, and creosote bush.
	West, bet. secs. 6 and 7. Over nearly level land, through scattered undergrowth, asc. 52 ft. over gradual NNE. slope.
9.70	Wash, 20 lks. wide, 2½ ft. deep, drains NNE.
17.40	Right bank of wash, 3 ft. deep, bears NNE. and SSW.
20.40	Left bank of wash, 4 ft. high, bears NNE. and SSW.
24.20	Wash, 50 lks. wide, 2 ft. deep, drains NNE.
29.50	Wash, 70 lks. wide, 2 ft. deep, drains NNE.
40.00	Point for the ¼ sec. cor. of secs. 6 and 7. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 26 S R 62 E S 6 ¼ S 7 1959
	Raise a mound of stone, 3½ ft. base, 2½ ft. high, N. of cor. Continue ascent; asc. 18 ft. over gradual NNE. slope.
54.10	Wash, 40 lks. wide, 3 ft. deep, drains NNE.
56.00	Top of ascent, slopes NNE., desc. 30 ft. over WNW. slope.
62.40	Right bank of wash, 3 ft. deep, bears N. and S.
66.00	Left bank of wash, 3 ft. high, bears N. and S.
80.00	Point for the 1/16 sec. cor. of secs. 6 and 7. Set an iron post, 30 ins. long, 2½ ins. diam., 2 ins. in the ground, to solid rock, and in a mound of stone to top, with brass cap mkd. T 26 S R 62 E S 6 1/16 ————— 80.00 S 7 1959
86.10	Wash, 150 lks. wide, 8 ft. deep, drains NE., asc. 118 ft. over SE. slope.
98.07	Intersect E. bdy. sec. 1, T. 26 S., R. 61 E.