

Independent Resurvey, E. Bdy., T. 17 S., R. 65 E.

Chains

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T17S
R65E R66E

$\frac{1}{2}$
S12 | S7
1959

Raise a mound of stone, $3\frac{1}{2}$ ft. base, W. of cor.

69.42 Intersect the Fourth Standard Parallel South.

Point for the closing cor. of secs. 7 and 12, T. 17 S., Rs. 65 and 66 E.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T16S R65E

S36
S12 | S7
C | C

R65E R66E

T17S

1959

Raise a mound of stone, $3\frac{1}{2}$ ft. base, south of cor.

From the closing cor. the standard $\frac{1}{2}$ sec. cor. on the S. bdy., sec. 36, T. 16 S., R. 65 E. bears E. 28.14 chs. dist., an iron post, 1 in. diam., set, mkd. and witnessed as described in the official record.

From the same cor., the standard cor. of secs. 35 and 36, T. 16 S., R. 65 E., bears W. 11.86 chs. dist., an iron post set, mkd, and witnessed as described in the official record.

Land, rolling desert.
Soil, shallow, gravelly.
Timber, none.

Independent Resurvey of Subdivision of Township 17 South, Range 65 East, Superseding the Survey Executed by U. S. Deputy Surveyor T. A. McGee in 1882

From the cor. of secs. 1, 2, 35 and 36, on the S. bdy. of T. 17 S., R. 65 E.

N. $0^{\circ} 01'$ W., bet. secs. 35 and 36, over rolling desert land, draining NW.; desc. 30 ft. over gentle NW. slope.

18.60 Wash, 2 ft. deep, 30 lks. wide, drains NW., cont. desc. 50 ft.

40.00 Point for the $\frac{1}{2}$ sec. cor. of secs. 35 and 36.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 16 ins. in the ground and in a mound of stone, $3\frac{1}{2}$ ft. base to cap, with brass cap mkd.

T17S R65E

$\frac{1}{2}$
S35 | S36
1959

Cont. desc. 60 ft.

78.40 Wash, 2 ft. deep, 20 lks. wide, drains NW.