

Independent Resurvey, Subdivision, T. 17 S., R. 65 E.

Chains

T17S R65E

S11|S12

S14|S13

1959

Land, nearly level.
Soil, shallow, gravelly.
Timber, none.

From the cor. of secs. 7, 12, 13 and 18, West, bet. secs. 12 and 13,
across nearly level land, draining NW.

3.70 Wash, 12 ins. deep, 30 lks. wide, drains N. 20° W.

14.30 Wash, 2 ft. deep, 20 lks. wide, drains N. 35° W.

39.98 Point for the $\frac{1}{4}$ sec. cor. of secs. 12 and 13.

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 22 ins. in the ground,
with brass cap mkd.

T17S R65E

 $\frac{1}{4}$ S12

S13

1959

Raise a mound of stone, 3 $\frac{1}{2}$ ft. base, 24 ins. high, N. of cor.

79.96 The cor. of secs. 11, 12, 13 and 14.

Land, nearly level desert.
Soil, shallow, gravelly.
Timber, none.

From the sec. cor. of secs. 11, 12, 13 and 14.

N. 0°01' W., bet. secs. 11 and 12, over nearly level desert land,
draining NW.; desc. 30 ft.

29.70 Wash, 1 ft. deep, 30 lks. wide, drains N. 75° W.

Cont. desc. 10 ft.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 11 and 12.

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 22 ins. in the ground,
with brass cap mkd.

T17S R65E

 $\frac{1}{4}$

S11|S12

1959

Raise a mound of stone, 3 $\frac{1}{2}$ ft. base, 20 ins. high, W. of cor.

Cont. desc. 30 ft.

69.45 Intersect the Fourth Standard Parallel South

Point for the closing cor. of secs. 11 and 12.

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 22 ins. in the ground,
with brass cap mkd.