

Independent Resurvey, Subdivision, T. 17 S., R. 65 E.

Chains

69.42

Intersect the Fourth Standard Parallel South

Point for the closing cor. of secs. 10 and 11.

Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T16S R65E

S34	
S10	S11
C	C
T17S	
1959	

Raise a mound of stone, 3½ ft. base, 20 ins. high, S. of cor.

From the closing cor., the standard ¼ sec. cor. on the S. bdy., sec. 34, T. 16 S., R. 65 E., bears E. 28.23 chms. dist., an iron post, 1 in. in diam., set, mkd., and witnessed as described in the official record.

From the same cor., the standard cor. of secs. 33 and 34, T. 16 S., R. 65 E., bears W. 11.77 chs. dist., an iron post, 2 ins. diam., set, mkd. and witnessed as described in the official record.

Land, nearly level desert.

Soil, shallow, gravelly.

Timber, none.

At midpoint bet. the closing cor. of secs. 10 and 11, and the closing cor. of secs. 11 and 12, T. 17 S., R. 65 E., set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, deposit charcoal in bottom of hole, with brass cap mkd.

¼S11	
T17S R65E	

No available stone to build mound.

From this cor. the standard ¼ sec. cor. on the S. bdy. of sec. 34, T. 16 S., R. 65 E., bears W. 11.84 chs. dist., an iron post 1 in. diam., set, mkd. and witnessed as described in the official record.

From the same cor. the standard sec. cor. of secs. 34 and 35, T. 16 S., R. 65 E. bears E. 28.16 chs. dist., an iron post 2 ins. diam., set, mkd. and witnessed as described in the official record.

From the cor. of secs. 3, 4, 33 and 34 on the S. bdy. of Tps. 17 and 18 S., R. 65 E., N. 0° 02' W., bet. secs. 33 and 34, over slightly rolling land, draining NW.

6.50 Unimproved road, bears N. 30° E. and S. 30° W.; desc. 30 ft.

33.00 Wash, 2 ft. deep, 20 lks. wide, drains NW.

40.00 Point for the ¼ sec. cor. of secs. 33 and 34.

Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T17S R65E

¼	
S33	S34
1959	