

Independent Resurvey, Subdivision, T. 17 S., R. 65 E.

Chains	T17S R65E $\frac{1}{2}$ S16 S15 1959 Desc. 30 ft. 80.00 Point for the cor. of secs. 9, 10, 15 and 16. Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground and in a collar of stone, with brass cap mkd. T17S R65E S9 S10 S16 S15 1959 Land, slightly rolling. Soil, shallow, gravelly. Timber, none.
	From the cor. of secs. 10, 11, 14 and 15, N. 89° 58' W., bet. secs. 10 and 15; desc. 30 ft. over rolling land; land drains NW. 37.60 Wash, 2 ft. deep, 20 lks. wide, drains N. 20° W. 39.95 Point for the ¼ sec. cor. of secs. 10 and 15. Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd. T17S R65E S10 $\frac{1}{4}$ S15 1959 Raise a mound of stone, 3½ ft. base, 24 ins. high, N. of cor.. Cont. slight descent, 10 ft. 79.90 The cor. of secs. 9, 10, 15 and 16. Land, rolling to nearly level. Soil, shallow, gravelly. Timber, none.
	N. 0° 02' W., bet. secs. 9 and 10, over nearly level land, draining NW.; desc. 20 ft. 40.00 Point for the ¼ sec. cor. of secs. 9 and 10. Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins in the ground, with brass cap mkd. T17S R65E $\frac{1}{4}$ S9 S10 1959 Raise a mound of stone, 3½ ft. base, 20 ins. high, W. of cor.; desc. 10 ft. 69.40 Intersect the Fourth Standard Parallel South. Point for the closing cor. of secs. 9 and 10, T. 17 S., R. 65 E.