

Independent Resurvey, Subdivision, T. 17 S., R. 65 E.

Chains	Raise a mound of stone, 3½ ft. base, 24 ins. high, W. of cor.
69.39	Intersect the Fourth Standard Parallel South.
	Point for the closing cor. of secs. 7 and 8.
	Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground and in a collar of stone, with brass cap mkd.
	T16S R65E S31 S7 S8 C C T17S 1959
	From the closing cor. of secs. 7 and 8, T. 17 S., R. 65 E., the standard ¼ cor. on the S. bdy. of sec. 31, T. 16 S., R. 65 E., bears E. 28.22 chs. dist., an iron post, 1 in. diam., set, mkd. and witnessed as recorded in the official record.
	From this same cor., the standard cor. of Tp. 16 S., Rs. 64 and 65 E., bears W. 11.78 chs. dist., an iron post, 2 ins. diam., set, mkd. and witnessed as recorded in the official record.
	Land, nearly level desert. Soil, shallow, gravelly. Timber, none.
	At midpoint bet. the closing cor. of secs. 7 and 8, and the closing cor. of secs. 8 and 9, T. 17 S., R. 65 E., set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.
	¼ S8 T17S R65E 1959
	Raise a mound of stone, 3½ ft. base, 24 ins. high, S. of cor.
	From this cor. the true point for standard ¼ sec. cor. on the S. bdy. of sec. 31, T. 16 S., R. 65 E., bears W. 11.78 chs. dist. and is witnessed E. 50 lks. dist. by an iron post, 1 in. diam., set, mkd. and witnessed as described in the official record.
	From the same cor. the standard cor. of secs. 31 and 32, T. 16 S., R. 65 E., bears E. 28.22 chs. dist., an iron post, 2 ins. diam., set, mkd. and witnessed as described in the official record.
	From the cor. of secs. 29, 30, 31 and 32.
	West, bet. secs. 30 and 31, over nearly level land, draining N.
	From the cor. of secs. 29, 30, 31 and 32, corral and windmill, bears S. 19° 58' W.; desc. 10 ft.
14.10	Wash, 1 ft. deep, 20 lks. wide, drains N. 30° E.
40.00	Point for the ¼ sec. cor. of secs. 30 and 31.
	Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground and in a collar of stone, with brass cap mkd.
	T17S R65E S30 ¼ S31 1959