

## Survey, S.. Bdy., T. 18 S., R. 65 E.

	Chains N. $89^{\circ} 58'$ W., bet. secs. 6 and 31. Asc. E. slope.
3.70	Draw, drains N.; asc. 115 ft. over E. slope.
12.20	Spur, projects NE.; desc. 200 ft. over NE. slope.
18.70	Draw, drains N.; desc. 200 ft. over NE. slope.
27.70	Draw, drains N.; cont. desc. 220 ft. along NE. slope.
37.60	Spur, bears E. and W.; asc. 30 ft. over E. slope.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 6 and 31.  Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 18 ins. in the ground, and in a collar of stone, with brass cap mkd.
	T18S R65E $\frac{1}{4}$ S31 S6 T19S 1959
	Raise a mound of stone, $3\frac{1}{2}$ ft. base, 24 ins. high, N. of cor. Asc. 10 ft. over E. slope.
41.70	S. slope of knoll; desc. 220 ft. over W. slope.
53.80	Draw, drains N.; asc. 90 ft. over E. slope.
59.70	Slope changes to N.; asc. 20 ft.
64.90	Crest of hill; desc. 200 ft. over W. slope.
79.18	The cor. of Tps. 18 and 19 S., and Rs. 64 and 65 E., monumented by a 3 in. iron post, set, mkd. and witnessed as described in the official record. Land, mountainous. Soil, rocky. Timber, none.

## Survey of the East Boundary of T. 18 S., R. 65 E.

	From the Tp. cor. of Tps. 18 and 19 S., Rs. 65 and 66 E., secs. 1, 6, 31 and 36.
	North bet. secs. 31 and 36;
	Desc. 120 ft. over NW. slope
30.90	Wash, 2 ft. deep, 30 lks. wide, drains S., $55^{\circ}$ W.; asc. S. slope.
35.10	American Borax Road, unimproved, bears N. $85^{\circ}$ W., and S. $85^{\circ}$ E.; asc. 40 ft.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 31 and 36.  Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 10 ins. in the ground to bedrock, and in a mound of stone, $3\frac{1}{2}$ ft. base to top of cap, with brass cap mkd.

T18S  
R65E R66E  
 $\frac{1}{4}$   
S36 S31  
1958