

Survey, E. Bdy., T. 18 S., R. 65 E.

Chains

80.00 Point for the cor. of secs. 1, 6, 7, and 12.

Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground, and in a mound of stone, 3½ ft. base 18 ins. high, with brass cap mkd.

T18S
R65E R66E
S1|S6
S12|S7
1959

Land, broken, mountainous.
Soil, rocky.
Timber, none.

North bet. secs. 1 and 6;

Desc. 40 ft. over N. slope.

2.00 Wash, 2 ft. deep, 1.00 ch. wide, drains W.; asc. 320 ft. over ledgy S. slope.

19.50 Spur, projects NW.; desc. 410 ft. over NE. slope.

34.70 Wash, in bottom of draw, drains W.; asc. 120 ft. over steep S. slope.

40.00 Point for the ¼ sec. cor. of secs. 1 and 6.

Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base to top of cap, with brass cap mkd.

T18S
R65E R66E
¼
S1|S6
1959

Asc. 20 ft. over S. slope.

41.50 Spur, projects W.; desc. 280 ft. over N. slope.

55.10 Wash, 2 ft. deep, 20 lks. wide, drains W.; asc. 80 ft. over S. slope.

61.80 Spur, projects W.; desc. 160 ft. along W. slope.

77.40 Small wash in bottom of draw, drains NW.; asc. 20 ft. over SW. slope.

79.41 Point for the Tp cor. of Tps. 17 and 18 S., Rs. 65 and 66 E., secs. 1, 6, 31 and 36.

Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground to bedrock, and in a mound of stone, 3½ ft. base to top of cap, with brass cap mkd.

T17S
R65E R66E
S36|S31
S 1 | S 6
T18S
1959

Land, high, mountainous.
Soil, rocky.
Timber, none.