

Independent Resurvey of the South Boundary, T. 17 S., R. 66 E.

Chains	
.40	Point selected for the witness cor. of secs. 5, 6, 31 and 32. Set an iron post, 30 ins. long, 2½ ins. diam., on solid bedrock, in a mound of stone, 4 ft. base to top, with brass cap mkd. T17S R66E S31 S32 S6 S5 W C T18S 1959 Desc. broken N. slope 80 ft.
11.40	Changes to steep W. slope; desc. 480 ft.
40.00	Point for the ¼ sec. cor. of secs. 6 and 31. Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top, with brass cap mkd.; desc. 110 ft. over W. slope. T17S R66E ¼ S31 S 6 T18S 1959 Desc. 110 ft. over W. slope.
57.30	Wash, 2 ft. deep, 20 lks. wide, drains N. 80° W.; desc. 10 ft.
68.90	Wash, 2 ft. deep, 20 lks. wide, drains N.
79.01	Intersect the Tp. cor. of Tps. 17 and 18 S., Rs. 65 and 66 E., an iron post, 2½ ins. diam., set, mkd. and witnessed as described in the field notes of T. 18 S., R. 65 E. surveyed concurrently under this same group. Land, broken to rolling. Soil, shallow, gravelly. Timber, none.

Independent Resurvey of the East Boundary, T. 17 S., R. 66 E.

	Superseding the survey executed by Deputy Surveyor W. H. Myrick in 1882. From the Tp. cor. of Tps. 17 and 18 S., Rs. 66 and 66½ E. North, bet. secs. 31 and 36, over rolling land draining E.; desc. 20 ft.
8.00	Small wash, drains NE.; asc. 10 ft.
16.00	Top of small divide draining NE. and S.; desc. 30 ft.
40.00	Point for the ¼ sec. cor. of secs. 31 and 36. Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground, in a mound of stone, 3½ ft. base to top, with brass cap mkd. T17S R66E R66½E ¼ S36 S31 1959 Desc. 30 ft. over NE. slope.