

## Independent Resurvey of the Subdivision of T. 17 S., R. 66 E.

Chains

Land, rolling.  
Soil, shallow, gravelly.  
Timber, none.

N. 0° 01' W., bet. secs. 11 and 12.

Over rolling desert land draining NE.; desc. 50 ft. over SE. slope.

33.90 Flat wash, 2.50 chs. wide, drains NE.; desc. 10 ft. over gentle NE. slope.

40.00 Point for the  $\frac{1}{4}$  sec. cor. of secs. 11 and 12.

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$  ins. diam., 22 ins. in the ground, with brass cap mkd.

T17S R66E

$\frac{1}{4}$   
S11 | S12  
1959

Raise a mound of stone, 3 ft. base, 24 ins. high, W. of cor.

Desc. 30 ft. over NE. slope.

58.00 Wash, drains N. 60° E.; asc. 10 ft. over S. slope.

69.49 Intersect the Fourth Standard Parallel South.

Point for the closing cor. of secs. 11 and 12.

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$  ins. diam., 16 ins. in the ground, in a mound of stone, 3 $\frac{1}{2}$  ft. base to top, with brass cap mkd.

T16S

S35

S11 | S12

G C

T17S R66E

1959

From the closing cor. the standard  $\frac{1}{4}$  sec. cor. on the S. bdy. of sec. 35, T. 16 S., R. 66 E. bears E. 29.38 chs. dist., an iron post, 1 in. diam., set, mkd. and witnessed as described in the official record.

From the same cor. the standard cor. of secs. 34 and 35, T. 16 S., R. 66 E., bears W. 10.62 chs. dist., an iron post, 2 ins. diam., set, mkd. and witnessed as described in the official record.

Land, rolling.  
Soil, shallow, gravelly.  
Timber, none.

At midpoint bet. the closing cor. of secs. 11 and 12 and the closing cor. of secs. 7 and 12, Tps. 17 S., Rs. 66 and 66 $\frac{1}{2}$ E., set an iron post, 30 ins. long, 2 $\frac{1}{2}$  ins. diam., 22 ins. in the ground, with brass cap mkd.

$\frac{1}{4}$  S12

T17S R66E

1959

Raise a mound of stone, 3 ft. base, 24 ins. high, S. of cor.