

84

## Independent Resurvey of the Subdivision of T. 17 S., R. 66 E.

Chains	
21.40	Wash, 2 ft. deep, 20 lks. wide, drains NE.; cont. ascent of 30 ft. over NE. slope.
25.50	Same wash, drains irregularly E.; asc. 100 ft. over SE. slope.
40.02	Point for the $\frac{1}{4}$ sec. cor. of secs. 11 and 14. Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 16 ins. in the ground, in a mound of stone, $3\frac{1}{2}$ ft. base to top, with brass cap mkd.
	T17S R66E $\frac{1}{4}$ S11 S14 1959
	Cont. ascent along SE. slope 410 ft.
65.70	Crest of hill, bears N. and S.; desc. 160 ft.
72.00	Head of draw, drains SE.; asc. 40 ft. over E. slope.
80.04	The cor. of secs. 10, 11, 14 and 15. Land, high and rolling. Soil, rocky. Timber, none.
	N. $0^{\circ} 01'$ W., bet. secs. 10 and 11. Desc. steep NW. slope 150 ft.
12.60	Head of draw, drains NW.; asc. 70 ft. over SW. slope.
18.00	Spur, slopes NW.; desc. 100 ft. over N. slope.
23.10	Draw, drains NW.; asc. 30 ft. over S. slope.
27.60	Spur, slopes NW.; desc. 80 ft. over N. slope.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 10 and 11. Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 18 ins. in the ground, in a collar of stone, with brass cap mkd.
	T17S R66E $\frac{1}{4}$ S10   S11 1959
	Cont. descent 20 ft.
46.70	Wash, 2 ft. deep, 30 lks. wide, drains E.; asc. 10 ft. over S. slope.
50.10	Narrow bench, bears NW. and SE.; desc. 20 ft.
54.60	Wash, 2 ft. deep, 20 lks. wide, drains SE.; asc. 170 ft. over SE. slope.
65.20	Spur, projects E.; desc. 60 ft. over NE. slope. Head of draw, drains SE.; asc. 30 ft. over S. slope.
69.57	Intersect the Fourth Standard Parallel South.