

Independent Resurvey of the Subdivision of T. 17 S., R. 66 E.

Chains	
17.50	Wash, drains NW.; cont. descent 50 ft.
31.70	Wash, drains NW.; asc. 10 ft. over NE. slope.
39.99	Point for the $\frac{1}{4}$ sec. cor. of secs. 10 and 15. Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 6 ins. in the ground to bedrock, in a mound of stone, 3 $\frac{1}{2}$ ft. base to top, with brass cap mkd. T17S R66E $\frac{1}{4}$ S10 S15 1959 Desc. along N. slope 10 ft.
43.20	Wash, drains N.; asc. 40 ft. along N. slope.
79.98	The cor. of secs. 9, 10, 15 and 16. Land, rolling. Soil, shallow, gravelly. Timber, none.
	N. 0° 02' W., bet. secs. 9 and 10. Desc. 20 ft. over N. slope.
4.10	Wash, 2 ft. deep, 20 lks. wide, drains E.; asc. 140 ft. over S. slope.
29.60	Spur, slopes SW.; desc. 30 ft. over NW. slope.
34.20	Wash, 2 ft. deep, 10 lks. wide, drains SW.; asc. 30 ft. over S. slope.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 9 and 10. Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., over solid bedrock, in a mound of stone, 3 $\frac{1}{2}$ ft. base to top, with brass cap mkd. T17S R66E $\frac{1}{4}$ S 9 S10 1959 Cont. asc. of 160 ft. along S. slope.
61.70	Spur, slopes SW.; desc. 30 ft. over N. slope.
69.59	Intersect the Fourth Standard Parallel South. Point for the closing cor. of secs. 9 and 10. Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 6 ins. in the ground to solid bedrock, in a mound of stone, 4 ft. base to top, with brass cap mkd. T16S S33 S 9 S10 C C T17S R66E 1959 From the closing cor. the standard $\frac{1}{4}$ sec. cor. on the S. bdy. of sec. 33, T. 16 S., R. 66 E. bears E. 29.48 chs. dist. an iron post, 1 in. diam., set, mkd. and witnessed as described in the official record.