

Independent Resurvey of the Subdivision of T. 17 S., R. 66 E.

Chains	
	N. 0° 03' W., bet. secs. 8 and 9.
	Desc. 60 ft. over gentle N. slope.
11.40	Wash, 2 ft. deep, 30 lks. wide, drains SW.; asc. 30 ft. over S. slope.
16.60	Spur, projects W.; desc. 70 ft. over N. slope.
36.50	Draw, drains W.; asc. 20 ft. over S. slope.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 8 and 9. Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., over solid bedrock, in a mound of stone, 3 $\frac{1}{2}$ ft. base to top, with brass cap mkd. T17S R66E. $\frac{1}{4}$ S8 S9 1959 Asc. 50 ft. over S. slope.
58.20	Top of ascent of rise, slopes W.; desc. 40 ft. over N. slope.
69.61	Intersect the Fourth Standard Parallel South. Point for the closing cor. of secs. 8 and 9. Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 8 ins. in the ground to bedrock, in a mound of stone, 3 $\frac{1}{2}$ ft. base to top, with brass cap mkd. T16S S32 S8 S9 C.C. R17S R66E 1959. From the closing cor. the standard $\frac{1}{4}$ sec. cor. on the S. bdy. of sec. 32, T. 16 S., R. 66 E., bears E. 29.50 chs. dist., an iron post, 1 in. diam., set, mkd. and witnessed as described in the official record. From the same cor. the standard cor. of secs. 31 and 32, T. 16 S., R. 66 E., bears W. 10.50 chs. dist., an iron post, 2 ins. diam., set, mkd. and witnessed as described in the official record. Land, rolling. Soil, shallow, gravelly. Timber, none.
	At midpoint bet. the closing cor. of secs. 8 and 9, and the closing cor. of secs. 9 and 10, T. 17 S., R. 66 E., set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap mkd. $\frac{1}{4}$ S9 T17S R66E 1959 Raise a mound of stone, 3 $\frac{1}{2}$ ft. base, 24 ins. high, S. of cor. From this cor. the standard $\frac{1}{4}$ sec. cor. on the S. bdy. of sec. 32, T. 16 S., R. 66 E., bears W. 10.51 chs. dist., an iron post, 1 in. diam., set, ; mkd. and witnessed as described in the official record.