

104

Independent Resurvey of the Subdivision of T. 17 S., R. 33 E.

Chains	From the cor. of secs. 7, 8, 17 and 18. N. 0° 03' W., bet. secs. 7 and 8.
	Desc. 10 ft. over NE. slope.
.50	Wash, 2 ft. deep, 1.00 chs. wide, drains N. 80° W.; asc. 160 ft. over S. slope.
16.30	Spur, projects SW.; desc. rocky NW. slope 180 ft.
35.00	Wash, drains NW.; asc. 20 ft. over SW. slope.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 7 and 8.
	Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.
	T17S R66E $\frac{1}{4}$ S7 S8 1959
	Raise a mound of stone, 3 ft. base, 22 ins. high, W. of cor.
	Desc. 40 ft. over N. slope.
54.50	Narrow wash, drains W.; asc. 30 ft. over S. slope.
65.10	Spur, slopes W.; desc. 40 ft. over N. slope.
69.52	Intersect the Fourth Standard Parallel South.
	Point for the closing cor. of secs. 7 and 8.
	Set an iron post, 30 ins. long, 2½ ins. diam., 12 ins. in the ground, in a mound of stone, 3½ ft. base to top, with brass cap mkd.
	T16S R66E S31 S7 S8 C C T17S R66E 1959
	From the closing cor. the standard $\frac{1}{4}$ sec. cor. on the S. bdy. of sec. 31, T. 16 S., R. 66 E. bears E. 29.55 chs. dist., an iron post, 1 in. diam., set, mkd. and witnessed as described in the official record.
	From the same cor. the standard cor. of secs. 31 and 36, T. 16 S., Rs. 65 and 66 E. bears W. 10.45 chs. dist., an iron post, 3 ins. diam. set, mkd. and witnessed as described in the official record.
	Land, high and rolling. Soil, rocky. Timber, none.
	At midpoint bet. the closing cor. of secs. 7 and 8 and the closing cor. of secs. 8 and 9, T. 17 S., R. 66 E., set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground, in a collar of stone, with brass cap mkd.
	$\frac{1}{4}$ S8 T17S R66E 1959
	From this cor. the standard $\frac{1}{4}$ sec. cor. on the S. bdy. of sec. 31, T. 16 S., R. 66 E. bears W. 10.48 chs. dist., an iron post, 1 in.