

## Independent Resurvey of the Subdivision of T. 17 S., R. 66 E.

diam., set, mkd. and witnessed as described in the official record.

From the same cor. the standard cor. of secs. 31 and 32, T. 16 S., R. 66 E. bears E. 29.52 chs. dist., an iron post, 2 ins. diam., set, mkd. and witnessed as described in the official record.

From the closing cor. of secs. 7 and 8, T. 17 S., R. 66 E., W. 40.00 chs. dist. on the N. bdy. of sec. 7, T. 17 S., R. 66 E., set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground, in a collar of stone, with brass cap mkd.

½ S7  
T17S R66E  
1959

From this cor. the standard ¼ sec. cor. on the S. bdy. of sec. 36, T. 16 S., R. 65 E. bears W. 10.45 chs. dist., an iron post, 1 in. diam., set, mkd. and witnessed as described in the official record.

From the same cor. the standard Tp. cor. of T. 16 S., Rs. 65 and 66 E. bears E. 29.55 chs. dist., an iron post, 3 ins. diam., set, mkd. and witnessed as described in the official record.

Survey of Patented Tract 38, T. 17 S., R. 66 E.  
Mineral Patent No. 014389

These claims were known as the Redwing and Dividend Nos. 1, 2, 3, 4, 5 and 6. The applicant was James Hooper Colton.

No evidence of the original monuments of the portion of this placer claim which consisted of lots 5 and 6, sec. 4, of the original survey of T. 17 S., R. 66 E. as shown on supplemental plat approved October 21, 1925, could be recovered.

Information as to recovered original cors. is limited to cors. indicated as found by U. S. G. S. and shown on their Moapa 4 Quadrangle. The cors. indicated as found are cors. of Tps. 15 and 16 S., Rs. 66 and 67 E., secs. 13, 14, 23 and 24, T. 16 S., R. 66 E., and the cor. of secs. 5, 6, 31 and 32, Tps. 15 and 16 S., R. 66 E. As these cors. closely conform to the independent resurvey in 1938 of the E. 5 miles of the Fourth Standard Parallel South through Range 66 East. These lots were restored at record bearing and dist. from the original standard corner of secs. 34 and 35, T. 16 S., R. 67 E.

At a point 15.84 chs. west of the true point for the standard cor. of secs. 33 and 34, T. 16 S., R. 66 E., record dist. for the original closing cor. of secs. 3 and 4, T. 17 S., R. 66 E.

Set an iron post, 30 ins. long, 2½ ins. diam., on solid rock, over a cross (X), and in a mound of stone, 4 ft. base, to top, with brass cap mkd.

AP 1  
TR38 S10  
T17S R66E  
1959

West, along Fourth Standard Parallel.