

Independent Resurvey, S. Bdy., T. 19 S., R. 66 E.

Chains

80.00

The corner of Tps. 19 and 20 S., Rs. 65 and 66 E., secs. 1, 6, 31, and 36;

An iron post, 3 ins. diam., set, marked and witnessed as described in the official record.

Land, broken.

Soil, rocky, sandstone outcroppings.

Timber, none.

Independent Resurvey of the East Boundary of T. 19 S., R. 66 E., Superseding the Survey Executed by Deputy Surveyor W. H. Myrick in 1882

From the corner of Tps. 19 and 20 S., R. 66 E., secs. 1 and 36;

North on the E. bdy. of sec. 36;

Desc. 110 ft. over rolling land draining N.

35.90

Wash, 2 ft. deep, 20 lks. wide, drains NE.; asc. 20 ft. over gentle S. slope.

40.00

Point for the $\frac{1}{4}$ sec. cor. of sec. 36.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, deposit charcoal in the bottom of the hole, with brass cap mkd.

T19S

R66E

 $\frac{1}{4}$

S36

1958

No stone available to build mound.

Asc. 70 ft. over S. slope.

53.00

Spur, slopes W.; desc. 120 ft. over NE. slope.

80.00

Point for the cor. of secs. 25 and 36.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, deposit charcoal in bottom of hole, with brass cap mkd.

T19S

R66E

S25

S36

1958

Land, rolling.

Soil, shallow, gravelly.

Timber, none.

North on the E. bdy. of sec. 25, T. 19 S., R. 66 E.

Desc. 20 ft. over N. slope.

6.80

Wash, 2 ft. deep, 60 lks. wide, drains N. 80° E., 3.00 chs., thence curves to the N.; desc. 30 ft. over N. slope.

39.80

Point selected for the witness $\frac{1}{4}$ sec. cor. for Sec. 25.