

Independent Resurvey, E. Bdy., T. 19 S., R. 66 E.

Chains

- 6.80 Top of high vertical ledge, bears E. and W.
Desc. 480 ft. along NE. slope.
- 40.00 Point for the $\frac{1}{4}$ sec. cor. of sec. 12.
Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 6 ins. in the ground to bedrock, and in a mound of stone, $4\frac{1}{2}$ ft. base to top of cap, with brass cap mkd.
- T19S
R66E
 $\frac{1}{4}$
S12
1958
- Cont. desc. 200 ft. over NE. slope.
- 55.70 Wash, 2 ft. deep, 20 lks. wide, drains NE.; asc. 60 ft. over SE. slope.
- 58.70 Spur, projects N. 80° E.; desc. 140 ft. over NE. slope.
- 64.60 Wash, 2 ft. deep, 20 lks. wide, drains N. 70° E.; asc. 50 ft. over SE slope.
- 67.00 Spur, slopes NE.; desc. 70 ft. over N. slope.
- 73.30 Wash, 2 ft. deep, 40 lks. wide, drains E.; desc. 60 ft. over NE. slope.
- 76.80 Small wash, drains E.; desc. 30 ft. over N. slope.
- 80.00 Point for the cor. of secs. 1 and 12.
Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 6 ins. in the ground to bedrock, and in a mound of stone, $4\frac{1}{2}$ ft. base to top of cap, with brass cap mkd.
- T19S
R66E
S1
S12
1958
- Land, broken.
Soil, rocky.
Timber, none.
-
- North on the E. bdy. of sec. 1.
Desc. 20 ft. over N. slope.
- .80 Wash in bottom of draw, drains E.; asc. 30 ft. over S. slope.
- 6.50 Spur, slopes E.; desc. 80 ft. over N. slope.
- 9.50 American Borax Road in wash, 2 ft. deep, 60 lks. wide, drains E.; asc. 430 ft. over S. slope.
- 40.00 Point for the $\frac{1}{4}$ sec. cor. of sec. 1.
Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 6 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base to top of cap, with brass cap mkd.