

140

## Survey of the Subdivision of T. 17 S., R. 66½ E.

Chains

Beginning at the cor. of secs. 25, 30, 31 and 36 on the W. bdy., monumented with an iron post, 2½ ins. diam., firmly set, mkd. and witnessed as described in the field notes of the concurrent resurvey of the E. bdy., T. 17 S., R. 66 E.

East, bet. secs. 30 and 31.

Over rolling land, through creosote brush.

40.00 Point for the ¼ sec. cor. of secs. 30 and 31.

Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground, and in a mound of stone, 3 ft. base to top, with brass cap mkd.

T17S R66½E  
¼ S30  
S31  
1959

Continue over rolling land.

51.43 Intersect the W. bdy. of T. 17 S., R. 67 E.

Point for the closing cor. of secs. 30 and 31.

Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground to solid rock, and in a mound of stone, 3 ft. base to top, with brass cap mkd.

T17S  
R66½E R67E  
S30 C | S19  
S31 C |  
1959

From this cor., the cor. of secs. 19 and 30, monumented by an iron post, 2½ ins. diam., firmly set, mkd. and witnessed as described in the field notes of the concurrent resurvey of the W. bdy. of T. 17 S., R. 67 E., bears S., 12.06 chs. dist.

Land, rolling.

Soil, rocky, sandy silt.

Timber, none; undergrowth, creosote brush, white sagebrush, mountain rush and cacti.

The point for the E. ¼ sec. cor. of sec. 31 is at midpoint and on the E. bdy. of the township.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 14 ins. in the ground to solid rock, and in a mound of stone, 2 ft. base to top, with brass cap mkd.

T17S  
R66½E  
¼ S31 |  
1959

From this cor., the ¼ sec. cor. of sec. 30, T. 17 S., R. 67 E., monumented by an iron post, 2½ ins. diam., firmly set, mkd. and witnessed as described in the field notes of the concurrent resurvey of the W. bdy. of T. 17 S., R. 67 E., bears S., 12.06 chs. dist.