

144

Survey of the Subdivision of T. 17 S., R. 66½ E.

Chains

T17S
R66½E
½ S18
W C
1959

From the true point for the E. ¼ sec. cor. of sec. 18, the ¼ sec. cor. of sec. 7, T. 17 S., R. 67 E., monumented by an iron post, 2½ ins. diam., firmly set, mkd. and witnessed as described in the field notes of the concurrent resurvey of the W. bdy. of T. 17 S., R. 67 E., bears S. 12.09 chs. dist.

The point for the E. ¼ sec. cor. of sec. 7 is 40.00 chs. N. of the closing cor. of secs. 7 and 18 and on the E. bdy. of the Tp.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground to solid rock, and in a mound of stone, 4 ft. base to top, with brass cap mkd.

T17S
R66½E R67E
½
S 7
1959

From this cor. the true point for the ¼ sec. cor. of sec. 6, T. 17 S., R. 67 E., bears S. 12.10 chs. dist. from which its witness cor. monumented by an iron post, 2½ ins. diam., firmly set, mkd. and witnessed as described in the field notes of the concurrent resurvey of the W. bdy. of T. 17 S., R. 67 E., bears N. 4.52 chs. dist.

The point for the N. ¼ sec. cor. of sec. 7 is 40.00 chs. E. of the closing cor. of secs. 7 and 12 and on the N. bdy. of the township (Fourth Standard Parallel South).

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground to solid rock, and in a mound of stone, 4 ft. base to top, with brass cap mkd.

T16S R66E

½ S 7
T17S R66½E
1959

From this cor. the standard ¼ sec. cor. of sec. 36, T. 16 S., R. 66 E., monumented by an iron post, 1 in. diam., conforming to the record, bears W. 10.66 chs. dist.