

183

Dependent Resurvey of a Portion of the Fourth Standard Parallel South  
through R. 67 E.

- 44.60 Bulldozed trail, bears NW. and SE.  
60.30 Bulldozed road, bears NW. and SE.; asc. 210 ft. over NE. slope.  
74.30 Overton Ridge, bears NW. and SE.; desc. 100 ft. over SW. slope.  
80.58 The standard cor. of secs. 34 and 35, mkd. by an iron post, 2 ins. diam., firmly set in the ground, with brass cap mkd. and witnessed as described in the official record.

Land, rolling.

Soil, rocky sandy silt.

Timber, none.

Undergrowth, creosote bush, mountain rush and cacti.

Dependent Resurvey of West Boundary, T. 17 S., R. 68 E.

Reestablishment of the survey executed by Woods and Myrick, Deputy Surveyors, in 1881.

From the cor. of Tps. 17 and 18 S., Rs. 67 and 68 E., which is mkd. by a limestone, 12x8x4 ins., firmly set in the ground and properly mkd. with a mound of stone 5 chs. W. This point will now function as the cor. of Tps. 17 and 18 S., R. 68 E., only.

Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.

	T17S	
R67E		R68E
S 1		S31
		S 6
	T18S	
	1958	

Deposit the original cornerstone alongside the iron post.

N. 0° 36' E., along the W. bdy. of sec. 31.

Over rolling land.

- 3.19 Point for the cor. of Tps. 17 and 18 S., R. 67 E., which is 240.00 chs. S. of the cor. of secs. 13, 18, 19 and 24.

At the cor. point.

Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground, in a mound of stone, 4 ft. base to top, with brass cap mkd.

	T17S	
R67E		R68E
S36		S31
S 1		
	T18S	
	1958	

Asc. 60 ft. over S. slope.

- 12.70 Spur, sloping W.; desc. 70 ft. over N. slope.  
20.65 Valley of Fire Wash, with small stream of water from spring approx. 5.00 chs. W., flowing E.; asc. 90 ft. over S. slope.  
40.80 Point for the ¼ sec. cor. of secs. 31 and 36, at proportionate dist.; there is no remaining evidence of the original cor. This point will now function as the ¼ sec. cor. of sec. 31, T. 18 S., R. 68 E. only.