

Dependent Resurvey of West Boundary, T. 17 S., R. 68 E.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground and in a collar of stone, with brass cap mkd.

T17S
R67E R68E
S1 | S6
 | S7
 1958

Deposit the original cornerstone alongside the iron post.

Land, rolling.

Soil, rocky and sandy silt.

Timber, none.

Undergrowth, creosote bush, mountain rush and cacti.

N. $0^{\circ} 22'$ W., along the W. bdy. of sec. 6.

Over rolling land, cut by deep washes.

- 3.00 By triangulation, desc. about 160 ft. over steep N. slope.
- 16.00 Wash, 1.00 ch. wide, 2 ft. deep, drains E.; asc. about 170 ft. over steep S. slope.
- 20.00 S. edge of bench, bears E. and W.
- 32.00 N. edge of bench, bears E. and W.; desc. about 100 ft. over steep N. slope.
- 34.00 Wash, 1.00 ch. wide, 2 ft. deep, drains E.; asc. about 100 ft. over steep s. slope.
- 36.00 End of triangulation on flat spur projecting E.
- 36.70 Point for the $\frac{1}{4}$ sec. cor. of sec. 1, T. 17 S., R. 67 E.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 18 ins. in the ground to the solid rock, in a mound of stone, 2 ft. base to top, with brass cap mkd.

T17S
R67E R68E
 $\frac{1}{4}$ |
S1 |
 1958

- 40.72 The $\frac{1}{4}$ sec. cor. of secs. 1 and 6, which is mkd. by a sandstone, 12x10x4 ins. firmly set and properly mkd. This point will now function as the $\frac{1}{4}$ sec. cor. of sec. 6, T. 17 S., R. 68 E. only.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 14 ins. in the ground to solid rock, in a mound of stone, 4 ft. base to top, with brass cap mkd.

T17S
R67E R68E
 |
 $\frac{1}{4}$
 | S6
 1958

Deposit the original cornerstone alongside the iron post.