

Dependent Resurvey of the West Boundary, T. 17 S., R. 68 E.

N. 0° 27' E., beginning new measurement.

Desc. 160 ft. over steep N. slope.

18.10 Wash, 50 lks. wide, 2 ft. deep, drains NE., thence over series of clay hills.

31.80 Nevada State Highway No. 12, black topped, bears SW. and NE.

37.62 The closing cor. of secs. 1 and 6, on the Fourth Standard Parallel South, which is mkd. by a limestone 12x10x6 ins. firmly set and properly mkd.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

T16S	R67E
S36	
—	
C	C
R67E	R68E
S1	S6
T17S	
1958	

Deposit the original cornerstone alongside the iron post.

From this cor. the standard Tp. cor. of Tps. 16 S., Rs. 67 and 68 E., hereinbefore described, bears S. 89° 59' E., 26.03 chs. dist.

Independent Resurvey of the South and West Boundaries and the
Subdivision of T. 17 S., R. 67 E.

Superseding the original survey by W. H. Myrick, Deputy Surveyor in 1882.

Beginning at the cor. of Tps. 17 and 18 S., R. 67 E. only, which is mkd. by an iron post, 2½ ins. diam., hereinbefore described.

West, bet. secs. 1 and 36.

Over rolling land, through desert shrubs; asc. 60 ft. over E. slope.

16.70 Ridge, bears N. and S.; desc. 60 ft. over W. slope.

28.00 Wash, 50 lks. wide, 2 ft. deep, drains NE.; asc. 40 ft. over E. slope.

32.85 E. edge of low mesa, thence over nearly level land.

37.64 Point for the ¼ sec. cor. of secs. 1 and 36, which is 40.00 chs. E. of the cor. of secs. 1, 2, 35 and 36.

Set an iron post, 30 ins. long, 2½ ins. diam., 8 ins. in the ground to solid rock, in a mound of stone, 4 ft. base to top, with brass cap mkd.

T17S	R67E
S36	
¼	
S1	
T18S	
1958	

38.20 W. edge of mesa, bears SW. and NE.; desc. 80 ft. over NW slope.