

Independent Resurvey of the South Boundary of T. 17 S., R. 67 E.

	Chains	Cont. over series of spurs and washes putting N.
54.70		Wash, 50 lks. wide, 2 ft. deep, drains N.; asc. 130 ft. over E. slope.
74.50		Spur, slopes N.; desc. 20 ft. over W. slope.
76.50		Wash, 30 lks. wide, 2 ft. deep, drains N.; thence along N. slope.
80.00		Point for the cor. of secs. 15, 6, 31 and 32. Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground to solid rock, in a mound of stone, 4 ft. base to top, with brass cap mkd.
		T17S R67E S31 S32 S6 S5 T18S 1958
		Land, series of spurs and washes. Soil, rocky and sandy clay silt. Timber, none. Undergrowth, creosote bush, mountain rush and cacti.
		West, bet. secs. 6 and 31.
		Over series of spurs and washes putting N. through desert shrubs.
13.80		Wash, 50 lks. wide, 2 ft. deep, drains N.; asc. 120 ft. over E. slope.
27.30		Rocky spur, projects N.; desc. 20 ft. over W. slope.
29.90		Wash, 3 lks. wide, 1 ft. deep, drains N.; asc. 85 ft. along N. slope.
40.00		Point for the ¼ sec. cor. of secs. 6 and 31.
		Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground to solid rock, in a mound of stone, 4 ft. base to top, with brass cap mkd.
		T17S R67E S31 S32 S6 S5 T18S 1958
		Cont. to ascent 150 ft. over boulder strewn N. slope.
55.30		Spur, slopes N.; deep erosional cut, 2.00 chs. S., thence along N. slope.
80.00		Spur, slopes N.
		Point for the cor. of Tps. 17 and 18 S., R. 67 E. only, at 400.00 chs. W. of the cor. of secs. 1, 2, 35 and 36 on the S. bdy. of the Tp.
		Set an iron post, 30 ins. long, 2½ ins. diam., 8 ins. in the ground to solid rock, in a mound of stone, 4 ft. base to top, with brass cap mkd.
		T17S R67E S31 S32 S6 S5 T18S 1958