

Independent Resurvey of Subdivisional Lines of T. 17 S., R. 67 E.

Chains	
59.50	Improved road, bears SW. and NE.; desc. 80 ft. over N. slope.
66.10	E. edge of mill dump.
66.84	Kaolin Wash, 1.00 ch. wide, 2 ft. deep, drains NE.; asc. 70 ft. over S. slope.
81.52	Intersect the Fourth Standard Parallel South.
	Point for the closing cor. of secs. 1 and 2.
	Set an iron post, 30 ins. long, 2½ ins. diam., 14 ins. in the ground to solid rock, in a mound of stone, 3 ft. base to top, with brass cap mkd.
	T16S R67E S35 S2 S1 C C T17S R67E 1958
	From this cor. the standard witness cor. of secs. 35 and 36, herinbefore described, bears S. 89° 59' E., 17.44 chs. dist.
	Land, rolling. Soil, sandy silt. Timber, none. Undergrowth, creosote bush, white sagebrush, mountain rush and cacti.
	The true point for the N. ¼ sec. cor. of sec. 1 is 40.00 chs. E. of the closing cor. of secs. 1 and 2, and on the N. bdy. of the Tp. (Fourth Standard Parallel South) and falls in small wash draining N. where the monument cannot be perpetuated.
	Thence N. 89° 59' W., .50 chs. dist.
	Point selected for the witness ¼ sec. cor. of sec. 1.
	Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, in a collar of stone, with brass cap mkd.
	T16S R67E ¼ S1 W C T17S R67E 1958
	From the true point for the N. ¼ sec. cor. of sec. 1 the standard ¼ sec. cor. of sec. 36, hereinbefore described, bears S. 89° 59' E., 19.03 chs. dist.
	From the cor. of secs. 2, 3, 34 and 35 on the S. bdy. of the Tp. N. 0° 01' W., bet. secs. 34 and 35.
	Over rolling land, through desert shrubs; desc. 40 ft. over NE. slope.
12.10	Wash, 1.50 chs. wide, 5 ft. deep, drains NE.; desc. 60 ft. over N. slope.
32.50	Wash, 1.00 ch. wide, 3 ft. deep, drains E.; asc. 70 ft. over S. slope.