

201

Independent Resurvey of Subdivisional Lines of T. 17 S., R. 67 E.

Chains

71.75 Kaolin Wash, 3.00 chs. wide, 4 ft. deep, drains SE.; asc. 50 ft. over SW. slope.

81.50 Intersect the Fourth Standard Parallel South.
Point for the closing cor. of secs. 2 and 3.
Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground to solid rock, in a mound of stone, 2 ft. base to top, with brass cap mkd.

T16S R67E
S34
C C
S3 S2
T17SS R67EE
1958

From this cor. the standard section cor. of secs. 34 and 35, which is mkd. by an iron post, 2 ins. diam., conforming to the record, bears E. 18.18 chs. dist.

Land, rolling.
Soil, shallow rocky sandy silt.
Timber, none.
Undergrowth, creosote bush, white sagebrush, mountain rush and cacti.

The point for the N. ¼ sec. cor. of sec. 2 is at midpoint and on the N. bdy. of the Tp. (Fourth Standard Parallel South).

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 14 ins. in the ground to solid rock, in a mound of stone, 4 ft. base to top, with brass cap mkd.

T16S R67E
¼ S2
T17S R67E
1959

From this cor. the standard ¼ sec. cor. of sec. 35, hereinbefore described, bears S. 89° 59' E., 18.46 chs. dist.

From the cor. of secs. 3, 4, 33 and 34, on the S. bdy. of the Tp.

N. 0° 01' W., bet. secs. 33 and 34.

Over rolling land; desc. 130 ft. over N. slope with series of washes draining E. and SE.

14.80 Wash, 1.00 ch. wide, 4 ft. deep, drains E.

16.40 Wash, 1.00 ch. wide, 3 ft. deep, drains E.

23.45 Wash, 1.50 chs. wide, 3 ft. deep, drains E.

35.05 Wash, 2.00 chs. wide, 5 ft. deep, drains SE.

40.00 Point for the ¼ sec. cor. of secs. 33 and 34.