

Independent Resurvey of Subdivisional Lines of T. 17 S., R. 67 E.

Chains	
	From the cor. of secs. 2, 3, 10 and 11.
	S. 89° 56' W., bet. secs. 3 and 10.
	Over broken land, through desert shrubs.
15.0	Wash, 1.00 ch. wide, 2 ft. deep, drains NE.; asc. 90 ft. along broken SE. slope.
39.99	Point for the $\frac{1}{4}$ sec. cor. of secs. 3 and 10.
	Set an iron post, 30 ins. long, 2½ ins. diam., 8 ins. in the ground to solid rock, in a mound of stone, 4 ft. base to top, with brass cap mkd.
	T17S R67E $\frac{1}{4}$ $\frac{S 3}{S10}$ 1958
	Asc. 120 ft. along broken SE. slope.
73.30	Broken spur sloping NE.; desc. 70 ft. over boulder strewn NW. slope.
79.98	The cor. of secs. 3, 4, 9 and 10.
	Land, broken.
	Soil, shallow sandy silt.
	Timber, none.
	Undergrowth, creosote bush, white sagebrush, mountain rush and cacti.
	N. 0° 01' W., bet. secs. 3 and 4.
	Over rolling land, through desert shrubs; desc. 90 ft. over NW. slope.
17.65	Wash, 2.50 chs. wide, 4 ft. deep, drains NE.; desc. 30 ft. over NW. slope.
29.60	Wash, 4.00 chs. wide, 4 ft. deep, drains NE.
36.50	Wash, 3.00 chs. wide, 4 ft. deep, drains SE.; asc. 40 ft. over SW. slope.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 3 and 4.
	Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.
	T17S R67E $\frac{1}{4}$ $\frac{S4}{S3}$ 1958
	At base of post, deposit sandstone, 10x6x6 ins., mkd. with a cross (X).
	Asc. 120 ft. over steep SW. slope.
54.50	Top of ascent on W. edge of spur sloping NE.; desc. 80 ft. over NW. slope.
81.59	Intersect the Fourth Standard Parallel South.