

Independent Resurvey of Subdivisional Lines of T. 17 S., R. 67 E.

Chains	
45.50	End of triangulation on sandstone spur sloping S.; desc. 40 ft. along steep S. slope.
48.00	Wash, 20 lks. wide, 2 ft. deep, drains SE.; asc. 50 ft. over E. slope.
79.67	<p>The cor. of secs. 6 and 7 on the W. bdy. of the Tp.</p> <p>Land, distorted sandstone formation. Soil, rocky sandy silt. Timber, none. Undergrowth, creosote bush, white sagebrush, mountain rush and cacti.</p>
	From the cor. of secs. 5, 6, 7 and 8.
	N. 0° 03' W., bet. secs. 5 and 6.
	Over distorted sandstone formation, through desert shrubs; asc. 10 ft. over S. facing ledge.
.30	Sandstone knob, thence by triangulation desc. about 200 ft. along ledgy W. slope.
25.50	Kaolin Wash, 1.50 chs. wide, 4 ft. deep, drains E.; asc. about 200 ft. along ledgy W. slope.
39.64	<p>Spur, projects W. from main spur to the E.</p> <p>Point selected for the witness $\frac{1}{2}$ sec. cor. of secs. 5 and 6.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground to solid rock, in a mound of stone, 4 ft. base to top, with brass cap mkd.</p>
	<p style="text-align: center;">T17S R67E W C $\frac{1}{2}$ S6↗S5 1959</p>
40.00	True point for the $\frac{1}{2}$ sec. cor. of secs. 5 and 6 falls on face of W. facing ledge where it is impractical to set the monument.
42.00	End of triangulation of W. edge of sandstone ridge, bears N. and S.; desc. 240 ft. along ledgy W. slope.
48.00	Base of sandstone ledges, bears irregularly N. and S.; thence over series of low sandstone spurs and ridges.
81.48	<p>Intersect the Fourth Standard Parallel South.</p> <p>True point for the closing cor. of secs. 5 and 6 falls in wash, 20 lks. wide, 2 ft. deep, draining NE. where the monument cannot be perpetuated.</p> <p>Thence East .42 chs. dist.</p> <p>Point selected for the witness closing cor. of secs. 5 and 6.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 8 ins. in the ground to solid rock, in a mound of stone, 4 ft. base to top, with brass cap mkd.</p>