300

678 b

<pre>in a mound of stone, 3 ft. base to top, with brass cap mkd.</pre>	3.	Independent Resurvey of the West Boundary of T. 17 S., R. 63 E.		
Set an iron post, 30 ins. long, 2½ ins. diam., 16 ins. in the gro in a mound of stone, 3 ft. base to top, with brass cap mkd. T175 R65B ½ 1518 5510 Cont. along rolling E. slope. Nash, 3 ft. deep, 50 lks. wide, drains S. 60° E1; cont. along E. 90.00 Foint for the cor. of secs. 7 and 18. Set an iron post, 30 ins. long, 2½ ins. diam., 12 ins. in the gro in a mound of stone, 3½ ft. base to top, with brass cap mkd. T173 R63E Set an iron post, 30 ins. long, 2½ ins. diam., 12 ins. in the gro in a mound of stone, 3½ ft. base to top, with brass cap mkd. T173 R63E Set an iron post, 30 ins. long, 2½ ins. diam., 12 ins. in the gro in a mound of stone, 3½ ft. base. North, along the W. bdy. of sec. 7. Over rolling desert general drainage E. Soil, shallow and gravelly. Timber, none. Undergrowth, creosote and black brush. North, along the W. bdy. of sec. 7. Over rolling desert land, through scattered undergrowth along E. 40.00 Point for the ½ sec. cor, on the W. bdy. of sec. 7. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the gro with brass cap mkd. T175 R63E 1958 Raise a mound of stone, 3 ft. base, 2½ ft. high, E. of cor.; cont along rolling E. slope. 56.00 Nash, 3 ft. deep, 50 lks. wide, drains E. irregularly. Jatersect the Fourth Standard Parallel South. Foint for the closing cor. of sec. 7, T. 17 S., K. 63 E.				
Set an iron post, 30 ins. long, 2½ ins. diam., 16 ins. in the gro in a mound of stone, 3 ft. base to top, with brass cap mkd. T175 R63E ½ 1518 1958 Cont. along rolling E. slope. 55.10 Wash, 3 ft. deep, 50 lks. wide, drains S. 60° E.; cont. along E. 67.90 Wash, 3 ft. deep, 60 lks. wide, drains E.; cont. along E. slope. 70.90 Wash, 2 ft. deep, 70 lks. wide, drains E.; cont. along E. slope. 80.00 Point for the cor. of secs. 7 and 18. Set an iron post, 30 ins. long, 2½ ins. diam., 12 ins. in the gro in a mound of stone, 3½ ft. base to top, with brass cap mkd. T175 R63E 80.00 Point for the cor. of secs. 7 and 18. Set an iron post, 30 ins. long, 2½ ins. diam., 12 ins. in the gro in a mound of stone, 3½ ft. base to top, with brass cap mkd. T178 R63E Land, rolling desert, general drainage E. Soil, shallow and gravelly. Timber, once. Undergrowth, creesote and black brush. North, along the W. bdy. of sec. 7. Over rolling desert land, through scattered undergrowth along E. 40.00 Point for the ½ sec. com, on the W. bdy. of sec. 7. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the gro with brass cap mkd. T178 R63E 4 175 863B Raise a mound of stone, 3 ft. base, 2½ ft. high, E. of cor.; cont along rolling E. slope. 56.00 Wash, 3 ft. deep, 50 lks. wide, drains E. irregularly. 56.11 Intersect the Fourth Standard Parallel South. Point for the closing cor. of sec. 7, T. 17 S., R., 63 E.			the second s	1 m
R63E \$18 1958 Cont. along rolling E. slope. 55.10 Wash, 3 ft. deep, 50 lks. wide, drains S. 60° E; cont. along E. 67.90 Wash, 3 ft. deep, 60 lks. wide, drains E.; cont. along E. slope. 70.90 Wash, 2 ft. deep, 70 lks. wide, drains E.; cont. along E. slope. 80.00 Point for the cor. of secs. 7 and 18. Set an iron post, 30 ins. long, 2½ ins. diam., 12 ins. in the growin a mound of stone, 3½ ft. base to top, with brass cap mkd. T175 R63E Soil, shallow and gravelly. Timber, none. Undergrowth, creosote and black brush. 7 Vorr rolling desert land, through scattered undergrowth along E. 40.00 Point for the ½ sec. cor, on the W. bdy. of sec. 7. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the growith brass cap mkd. T175 R638 ½ 157 158 R638 ½ 157 158 Raise a mound of stone, 3 ft. base, 2½ ft. high, E. of cor.; cont along rolling E. slope. 56.00 Wash, 3 ft. deep, 5	ound,	Set an iron post, 30 ins. long, 2½ ins. diam., 16 ins. in the ground		
 i958 Cont. along rolling E. slope. 55.10 Wash, 3 ft. deep, 50 lks. wide, drains S. 60° Ei; cont. along E. 67.90 Wash, 2 ft. deep, 70 lks. wide, drains E.; cont. along E. slope. 80.00 Point for the cor. of secs. 7 and 18. Set an iron post, 30 ins. long, 2½ ins. diam., 12 ins. in the gro in a mound of stone, 3½ ft. base to top, with brass cap mkd. T178 K63E S / Sla 1958 Land, rolling desert, general drainage E. Soil, shallow and gravelly. Timber, none. Undergrowth, creosote and black brush. North, along the W. bdy. of sec. 7. Over rolling desert land, through scattered undergrowth along E. 40.00 Point for the ½ sec. cor. on the W. bdy. of sec. 7. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the gro with brass cap mkd. T175 R638 Raise a mound of stone, 3 ft. base, 2½ ft. high, E. of cor.; cont along rolling E. slope. 56.00 Wash, 3 ft. deep, 50 lks. wide, drains E. irregularly. Intersect the Fourth Standard Parallel South. Point for the closing cor. of sec. 7, T. 17 S., R, 63 E. 		R63E		į
<pre>Cont. along rolling E. slope. S5.10 Wash, 3 ft. deep, 50 lks. wide, drains S. 60° E1; cont. along E. 67.90 Wash, 3 ft. deep, 60 lks. wide, drains E.; cont. along E. slope. 70.90 Wash, 2 ft. deep, 70 lks. wide, drains E.; cont. along E. slope. 80.00 Point for the cor. of secs. 7 and 18. Set an iron post, 30 ins. long, 2½ ins. diam., 12 ins. in the gro in a mound of stone, 3½ ft. base to top, with brass cap mkd. T175 K63E Soil, shallow and gravelly. Timber, none. Undergrowth, creosote and black brush. North, along the W. bdy. of sec. 7. Over rolling desert land, through scattered undergrowth along E. 40.00 Point for the ½ sec. coq. on the W. bdy. of sec. 7. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the gro with brass cap mkd. T175 R63E k 1958 Raise a mound of stone, 3 ft. base, 2½ ft. high, E. of cor.; cont along rolling E. slope. 56.00 Wash, 3 ft. deep, 50 lks. wide, drains E. irregularly. 69.12 Intersect the Fourth Standard Parallel South. Point for the closing cor. of sec. 7, T. 17 S., R, 63 E.</pre>				2
 55.10 Wash, 3 ft. deep, 50 lks. wide, drains S. 60° El; cont. along E. 67.90 Wash, 3 ft. deep, 60 lks. wide, drains E.; cont. along E. slope. 70.90 Wash, 2 ft. deep, 70 lks. wide, drains E.; cont. along E. slope. 80.00 Point for the cor. of secs. 7 and 18. Set an iron post, 30 ins. long, 2½ ins. diam., 12 ins. in the gro in a mound of stone, 3½ ft. base to cop, with brass cap mkd. 173 R63E Soil, shallow and gravelly. Timber, none. Undergrowth, creosote and black brush. North, along the W. bdy. of sec. 7. Over rolling desert land, through scattered undergrowth along E. 40.00 Point for the ½ sec. cor. on the W. bdy. of sec. 7. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the gro with brass cap mkd. 1175 R63E ½ 1 863E Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the gro with brass cap mkd. 1175 R63E ½ 1 958 Raise a mound of stone, 3 ft. base, 2½ ft. high, E. of cor.; cont along rolling E. slope. 56.00 Wash, 3 ft. deep, 50 lks. wide, drains E. irregularly. 69.12 Intersect the Fourth Standard Parallel South. Point for the closing cor. of sec. 7, T. 17 S., R. 63 E.		Cont. along rolling E. slope.		a X
 70.90 Wash, 2 ft. deep, 70 lks. wide, drains E.; cont. along E. slope. 80.00 Point for the cor. of secs. 7 and 18. Set an iron post, 30 ins. long, 2½ ins. diam., 12 ins. in the gro in a mound of stone, 3½ ft. base to top, with brass cap mkd. T175 R63E S.7 S18 1958 Land, rolling desert, general drainage E. Soil, shallow and gravelly. Timber, none. Undergrowth, creosote and black brush. North, along the W. bdy. of sec. 7. Over rolling desert land, through scattered undergrowth along E. 40.00 Point for the ½ sec. cor. on the W. bdy. of sec. 7. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the growith brass cap mkd. T175 R63E §7 1958 Raise a mound of stone, 3 ft. base, 2½ ft. high, E. of cor.; cont along rolling E. slope. 56.00 Wash, 3 ft. deep, 50 lks. wide, drains E. irregularly. 69.12 Intersect the Fourth Standard Parallel South. Point for the closing cor. of sec. 7, T. 17 S., R. 63 E. 	slope.		55.10	
 80.00 Point for the cor. of secs. 7 and 18. Set an iron post, 30 ins. long, 2½ ins. diam., 12 ins. in the gro in a mound of stone, 3½ ft. base to top, with brass cap mkd. T175 R63E S.7 S18 1958 Land, rolling desert, general drainage E. Soil, shallow and gravelly. Timber, none. Undergrowth, creosote and black brush. North, along the W. bdy. of sec. 7. Over rolling desert land, through scattered undergrowth along E. 40.00 Point for the ½ sec. cor. on the W. bdy. of sec. 7. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the gro with brass cap mkd. T175 R63E ½ 7 Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the gro with brass cap mkd. 56.00 Wash, 3 ft. deep, 50 lks. wide, drains E. irregularly. 69.12 Intersect the Fourth Standard Parallel South. Point for the closing cor. of sec. 7, T. 17 S., R. 63 E.	2			
Set an iron post, 30 ins. long, 2½ ins. diam., 12 ins. in the gro in a mound of stone, 3½ ft. base to top, with brass cap mkd. T173 R63E R63E Soil, shallow and gravelly. Timber, none. Undergrowth, creosote and black brush. North, along the W. bdy. of sec. 7. Over rolling desert land, through scattered undergrowth along E. 40.00 Point for the ½ sec. cor. on the W. bdy. of sec. 7. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the gro with brass cap mkd. T175 R63E ½ Soil R63E 56.00 Wash, 3 ft. deep, 50 lks. wide, drains E. irregularly. 69.12 Intersect the Fourth Standard Parallel South. Point for the closing cor. of sec. 7, T. 17 S., R. 63 E.				1
 in a mound of stone, 3½ ft. base to top, with brass cap mkd. T175 R63E S 7 S18 1958 Land, rolling desert, general drainage E. Soil, shallow and gravelly. Timber, none. Undergrowth, creosote and black brush. North, along the W. bdy. of sec. 7. Over rolling desert land, through scattered undergrowth along E. 40.00 Point for the ½ sec. cor. on the W. bdy. of sec. 7. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the gro with brass cap mkd. T175 R63E ½ Raise a mound of stone, 3 ft. base, 2½ ft. high, E. of cor.; cont along rolling E. slope. 56.00 Wash, 3 ft. deep, 50 lks. wide, drains E. irregularly. 69.12 Intersect the Fourth Standard Parallel South. Point for the closing cor. of sec. 7, T. 17 S., R. 63 E. 			80.00	£
 T175 R63E S 7 Soil, shallow and gravelly. Timber, none. Undergrowth, creosote and black brush. North, along the W. bdy. of sec. 7. Over rolling desert land, through scattered undergrowth along E. 40.00 Point for the ½ sec. cor. on the W. bdy. of sec. 7. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the growith brass cap mkd. T178 R638 §7 1958 Raise a mound of stone, 3 ft. base, 2½ ft. high, E. of cor.; cont along rolling E. slope. 56.00 Wash, 3 ft. deep, 50 lks. wide, drains E. irregularly. 69.12 Intersect the Fourth Standard Parallel South. Point for the closing cor. of sec. 7, T. 17 S., R. 63 E. 	ound,		(No.) is no.)	
Is 7 SIB 1958 Land, rolling desert, general drainage E. Soil, shallow and gravelly. Timber, none. Undergrowth, creosote and black brush. North, along the W. bdy. of sec. 7. Over rolling desert land, through scattered undergrowth along E. 40.00 Point for the ½ sec. cor. on the W. bdy. of sec. 7. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the growith brass cap mkd. TI75 R63E ½ 1958 Raise a mound of stone, 3 ft. base, 2½ ft. high, E. of cor.; cont along rolling E. slope. 56.00 Wash, 3 ft. deep, 50 lks. wide, drains E. irregularly. Foint for the Closing cor. of sec. 7, T. 17 S., R. 63 E.		T17S		e T
 1958. Land, rolling desert, general drainage E. Soil, shallow and gravelly. Timber, none. Undergrowth, creosote and black brush. North, along the W. bdy. of sec. 7. Over rolling desert land, through scattered undergrowth along E. 40.00 Point for the ½ sec. cor. on the W. bdy. of sec. 7. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the gro with brass cap mkd. TI75 R63E ½ 1958 Raise a mound of stone, 3 ft. base, 2½ ft. high, E. of cor.; cont along rolling E. slope. 56.00 Wash, 3 ft. deep, 50 lks. wide, drains E. irregularly. 69.12 Intersect the Fourth Standard Parallel South. Point for the closing cor. of sec. 7, T. 17 S., R. 63 E. 		<u>S 7</u>		
 Soil, shallow and gravelly. Timber, none. Undergrowth, creosote and black brush. North, along the W. bdy. of sec. 7. Over rolling desert land, through scattered undergrowth along E. 40.00 Point for the ½ sec. cor. on the W. bdy. of sec. 7. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the growith brass cap mkd. TI7S R63E ½ 1958 Raise a mound of stone, 3 ft. base, 2½ ft. high, E. of cor.; cont along rolling E. slope. 56.00 Wash, 3 ft. deep, 50 lks. wide, drains E. irregularly. 69.12 Intersect the Fourth Standard Parallel South. Point for the closing cor. of sec. 7, T. 17 S., R. 63 E. 				
 North, along the W. bdy. of sec. 7. Over rolling desert land, through scattered undergrowth along E. 40.00 Point for the ½ sec. cor. on the W. bdy. of sec. 7. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the growith brass cap mkd. T175 R63E ½ §7 1958 Raise a mound of stone, 3 ft. base, 2½ ft. high, E. of cor.; cont along rolling E. slope. 56.00 Wash, 3 ft. deep, 50 lks. wide, drains E. irregularly. 69.12 Intersect the Fourth Standard Parallel South. Point for the closing cor. of sec. 7, T. 17 S., R. 63 E. 		Soil, shallow and gravelly. Timber, none.		
 North, along the W. bdy. of sec. 7. Over rolling desert land, through scattered undergrowth along E. 40.00 Point for the ½ sec. cor. on the W. bdy. of sec. 7. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the growith brass cap mkd. T17S R63E §7 1958 Raise a mound of stone, 3 ft. base, 2½ ft. high, E. of cor.; cont along rolling E. slope. 56.00. Wash, 3 ft. deep, 50 lks. wide, drains E. irregularly. 69.12 Intersect the Fourth Standard Parallel South. Point for the closing cor. of sec. 7, T. 17 S., R. 63 E. 	1.2	Undergrowth, creosote and black brush.	1.1	
 North, along the W. bdy. of sec. 7. Over rolling desert land, through scattered undergrowth along E. 40.00 Point for the ½ sec. cor. on the W. bdy. of sec. 7. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the growith brass cap mkd. T17S R63E §7 1958 Raise a mound of stone, 3 ft. base, 2½ ft. high, E. of cor.; cont along rolling E. slope. 56.00. Wash, 3 ft. deep, 50 lks. wide, drains E. irregularly. 69.12 Intersect the Fourth Standard Parallel South. Point for the closing cor. of sec. 7, T. 17 S., R. 63 E. 				÷.
 Over rolling desert land, through scattered undergrowth along E. 40.00 Point for the ½ sec. cor, on the W. bdy. of sec. 7. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the gro with brass cap mkd. T175 R63E ½ S7 1958 Raise a mound of stone, 3 ft. base, 2½ ft. high, E. of cor.; cont along rolling E. slope. 56.00 Wash, 3 ft. deep, 50 lks. wide, drains E. irregularly. 69.12 Intersect the Fourth Standard Parallel South. Point for the closing cor. of sec. 7, T. 17 S., R. 63 E. 		North, along the W. bdy. of sec. 7.		
 40.00 Point for the ½ sec. cor, on the W. bdy. of sec. 7. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the growith brass cap mkd. T17S R63E ½ S7 1958 Raise a mound of stone, 3 ft. base, 2½ ft. high, E. of cor.; cont along rolling E. slope. 56.00 Wash, 3 ft. deep, 50 lks. wide, drains E. irregularly. 69.12 Intersect the Fourth Standard Parallel South. Point for the closing cor. of sec. 7, T. 17 S., R. 63 E. 	slope.	Over rolling desert land, through scattered undergrowth along E. sl		
 Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the gro with brass cap mkd. T17S R63E ¹/₄ [S7 1958 Raise a mound of stone, 3 ft. base, 2½ ft. high, E. of cor.; cont along rolling E. slope. 56.00 Wash, 3 ft. deep, 50 lks. wide, drains E. irregularly. 69.12 Intersect the Fourth Standard Parallel South. Point for the closing cor. of sec. 7, T. 17 S., R. 63 E. 		40.00 Point for the $\frac{1}{4}$ sec. cor. on the W. bdy. of sec. 7.		
R63E k S7 1958 Raise a mound of stone, 3 ft. base, 2½ ft. high, E. of cor.; cont along rolling E. slope. 56.00 Wash, 3 ft. deep, 50 lks. wide, drains E. irregularly. 69.12 Intersect the Fourth Standard Parallel South. Point for the closing cor. of sec. 7, T. 17 S., R. 63 E.	und,	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground		
 S7 1958 Raise a mound of stone, 3 ft. base, 2½ ft. high, E. of cor.; cont along rolling E. slope. 56.00 Wash, 3 ft. deep, 50 lks. wide, drains E. irregularly. 69.12 Intersect the Fourth Standard Parallel South. Point for the closing cor. of sec. 7, T. 17 S., R. 63 E. 				
 along rolling E. slope. 56.00. Wash, 3 ft. deep, 50 lks. wide, drains E. irregularly. 69.12 Intersect the Fourth Standard Parallel South. Point for the closing cor. of sec. 7, T. 17 S., R. 63 E. 		S7		
69.12 Intersect the Fourth Standard Parallel South. Point for the closing cor. of sec. 7, T. 17 S., R. 63 E.	•	Raise a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft. high, E. of cor.; cont. along rolling E. slope.		4 V
Point for the closing cor. of sec. 7, T. 17 S., R. 63 E.		56.00 Wash, 3 ft. deep, 50 lks. wide, drains E. irregularly.	56.00 .	
Point for the closing cor. of sec. 7, T. 17 S., R. 63 E.			69.12	
Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 12 ins. in the group		Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 12 ins. in the groun in a mound of stone, $3\frac{1}{2}$ ft. base, 14 ins. high, with brass cap mkd.		
TI6S R62E				
S7 T17S R63E 1958		T_{R63E}		

U. S. GOVERNMENT PRINTING OFFICE

28520-2

16

-4