

318

Independent Resurvey of the Subdivision of T. 17 S., R. 63 E.

Chains	
40.03	Point for the $\frac{1}{4}$ sec. cor. of secs. 10 and 15.
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., over a cross (X) cut on solid rock, in a mound of stone, 4 ft. base to top, with brass cap mkd.
	T17S R63E $\frac{1}{4}$ S10 S15 1958
	Asc. 80 ft. over ledgy SE. slope.
44.50	Spur, slopes S.; desc. 140 ft. over SW. slope.
58.50	Wash, drains S.; asc. 150 ft. over E. slope.
64.00	Spur, slopes S.; cont. along broken S. slope.
73.50	Base of steep E. slope; asc. 250 ft.
80.06	The cor. of secs. 9, 10, 15 and 16.
	Land, broken. Soil, rocky and gravelly. Timber, none. Undergrowth, creosote bush.
	N. 0° 02' W., bet. secs. 9 and 10.
	Over broken mountainous desert land; asc. 200 ft. along broken E. slope.
14.80	Ridge, bears N. and S. irregularly; desc. 180 ft. along broken W. slope.
27.40	Base of steep descent, bears N. and SW.; desc. 10 ft. over gentle W. slope.
35.40	Wash, 2 ft. deep, 30 lks. wide, drains S. 30° W.; asc. 25 ft. over E. slope.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 9 and 10.
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T17S R63E $\frac{1}{4}$ S 9 S10 1958
	Raise a mound of stone, $3\frac{1}{2}$ ft. base, 24 ins. high, W. of cor.; asc. 30 ft. along E. slope.
48.00	Base of steep ascent, bears E. and NW.; asc. 300 ft. over broken SW. slope.
68.95	Point for the closing cor. of secs. 9 and 10 falls on ledge facing W. and cannot be monumented.
	The point selected for the witness closing cor. of secs. 9 and 10 bears W. 5 lks. dist. at this point.